

## CLEVERTRONICS LP ULTRABLADE PRO SURFACE MOUNT, THEATRE



### PRODUCT INFORMATION

Part Number	CUBPRO-SM-TH-R
Description	LP Premium Ultrablade Pro surface mount blade Exit, Theatre
Construction	PC/ABS body with PC diffuser
Mounting	Wall, ceiling single-sided & ceiling double-sided
Dimensions L x W x H	317mm x 157mm x 8.7mm (Blade Assembly) 360mm x 72mm x 47mm (Base)
Weight	1.0kg
Operating Mode	Maintained
Testing System	Clevertest Plus Enabled (Not activated by default)
Battery	Lithium Iron Phosphate, 3.2V 1100mAh
Charging Method	Intelligent current limited constant voltage
Diffuser	Theatre mask, Running man (Must specify diffuser combination)
Lamp(s)	12 x LED, 100,000 hours
Operating Voltage	240V AC; 50Hz
Power Consumption	1.4 Watts (Standby), 3.7 Watts (Max)
IP Rating	IP20
Operating Temperature	1°C to 40°C
AS2293 Classification	C <sub>0</sub> =N/A C <sub>90</sub> =N/A
Viewing Distance	24m

### REPLACEMENT PARTS

PART NUMBER	DESCRIPTION
1550105	BATT:LP 3.2V 1100mAh 260mm lead,no BRKT
8002178	PCA:LL-Pro L10 2pinML 60mA .#CT10142-L5
8002945	PCA:C/LUBPRO-SM #CT10142-L8 CTP

