

CLEVERTRONICS LP ODYSSEY QUANTUM LED DIFFUSED BATTEN



PRODUCT INFORMATION

Catalogue Number	CBS4LEDS-LO-DIF
MIC	AUB02310090001
Description	LP Premium Quantum LED diffused batten with LED Emergency Pod, Enabled with Clevertest Plus
Construction	Powder coated steel body with acrylic prismatic diffuser and PC/ABS end caps
Mounting	Surface Mount
Dimensions L x W x H	1274mm x 120mm x 110mm
Operating Mode	Sustained
Testing System	Clevertest Plus Enabled (Not activated by default)
Battery	Lithium Iron Phosphate
Charging Method	Intelligent Current Limited Constant Voltage
Diffuser	Acrylic Prismatic
Driver / Ballast	21w 700mA, 50,000hr
Lamp(s)	LED strip module, 4,000K natural white, 50,000h life [L70/B50 Ta 40°C], Ra>80
Operating Voltage	220-240V AC; 50Hz
Power Factor	0.95
Total lumen output	2250lm @118lm/W
Power Consumption	19 Watts (Lamps ON), 0.4 Watts (Lamps OFF)
IP Rating	IP20
Operating Temperature	1°C to 40°C
AS2293 Classification	C ₀ =D40 C ₉₀ =D40

REPLACEMENT PARTS

PART NUMBER	DESCRIPTION
1550050	BATT:LP 3.2V 3200mAh 70mm lead,no BRKT.
8002695	PCA:LED Strip 8S6P, ALS-13-840-0-02-B
1330023	LED Driver – 21w 700mA,220-240V
CLIFE-CKIT-NP	Lifelight, Control Only, LP, No Plug

The product details described in this document are current as at the version date of the document. We reserve the right to change product design, specifications or materials (Specifications) as part of our continuous improvement program. Please confirm the applicable Specifications at the time of placing your order