

**LWB4N-P-ZW**

## CLEVERTRONICS L10 1200mm (4ft) NON-MAINTAINED WEATHERPROOF BATTEN REPLACEMENT



Gen 1



Gen 2

Fittings are supplied without tubes

### PRODUCT INFORMATION

Catalogue Number	LWB4N-P-ZW
Description	L10 Optimum Weatherproof Batten Emergency with LED Emergency POD
Construction	Polycarbonate Base and Diffuser with Powdercoated Metal Gear Tray and Tamper proof Stainless Steel clips
Mounting	Surface Mount
Dimensions L x W x H	1330mm x 160mm x 110mm
Weight	3.4kg
Operating Mode	Non-maintained
Testing System	Zoneworks computerised testing
Battery	Lithium Nanophosphate, 3.3V 2500mAh
Charging Method	Intelligent Current Limited Constant Voltage
Diffuser	Polycarbonate
Lamp(s)	2 x 3W LED
Operating Voltage	240V AC; 50Hz
Power Consumption	0.4 Watts (Standby), 4.7 Watts (Max)
IP Rating	IP65
Operating Temperature	0°C to 40°C
AS2293 Classification	C <sub>0</sub> =D63 C <sub>90</sub> =D50 (Gen 1) C <sub>0</sub> =D80 C <sub>90</sub> =D80 (Gen 2)
Impact Rating	IK08

### REPLACEMENT PARTS

PART NUMBER	DESCRIPTION
1530050	BATTERY:L10 3.3V 2.5AH 70mm lead,noBRKT
LLIFE-PRO-CKIT-NP	LifelightPro,Control Only,Batten,L10, NP
8001450	PCA:Powerline Node ZW, #CT10310-A6

