

CLEVERTRONICS LP LIFELIGHT PRO CYLINDER SURFACE MOUNT



PRODUCT INFORMATION

Part Number	CLIFE-PRO-SMC-BLK
MIC	AUT02310160001
Description	LP Premium LifeLight PRO, high performance, cylinder surface mounted Emergency Light, Black, Enabled with Clevertest Plus
Construction	Powder coated metal enclosure
Mounting	Surface mount
Dimensions L x W x H	102mm Diameter x 280mm Height
Weight	1.5kg
Operating Mode	Non-maintained
Testing System	Clevertest Plus Enabled (Not activated by default)
Battery	Lithium Iron Phosphate, 3.2V 6400mAh
Charging Method	Intelligent current limited constant voltage
Lamp(s)	Dual LED (Lifetime warranty on the lamp head and loom assembly)
Operating Voltage	240V AC; 50Hz
Power Consumption	0.4 Watts (Standby), 2.7 Watts (Max)
IP Rating	IP20
Operating Temperature	1°C to 40°C
AS2293 Classification	C ₀ =D63 C ₉₀ =D63

REPLACEMENT PARTS

PART NUMBER	DESCRIPTION
1550230	BATT:LP 3.2V 6400mAh.200mm lead.Brkt.
AUM02370220001 CLIFE-PRO-SMC-CKIT-NP	LifelightPro,Control Only, SMC, LP, NP, OWC
1100842	Lifelight Pro Head Assbly,Ld:280mm,Round,Blk,Gen 2

The product details described in this document are current as at the version date of the document. We reserve the right to change product design, specifications or materials (Specifications) as part of our continuous improvement program. Please confirm the applicable Specifications at the time of placing your order.