



FVP4LED-P

CLEVERTRONICS 240V ARGONAUT VANDAL BATTEN



PRODUCT INFORMATION

Part Number	FVP4LED-P
MIC	AUB04630010003
Description	240V 4ft Argonaut LED Vandal Batten
Construction	Pressure Die-cast, Low Copper Aluminium Alloy Body with Grey Powder Coat Paint Finish. Removable Gear Tray and Replaceable LED Modules.
Mounting	Surface Mount
Dimensions L x W x H	1320mm x 140mm x 120mm
Diffuser	Opal, Impact Resistant Polycarbonate with Secure Access Screws (LSZH)
Driver / Ballast	Tridonic LC 50W 350-1050mA
Lamp(s)	2 x LED module, 4000K natural white, 100,000h [L80/ B20, Ta 40°C], Ra>80
Operating Voltage	240V AC; 50Hz
Power Factor	0.95
Total lumen output	5135 lm @ 118lm/W
Power Consumption	43.5 Watts
IP Rating	IP66
Operating Temperature	-25°C to 40°C
Impact Rating	IK10
Applicable Standards	AS/NZS3820, CISPR15, AS/NZS60598.1
Compliance Marking (RCM)	

REPLACEMENT PARTS

PART NUMBER	DESCRIPTION
1330055	LED Driver - LC 50w 350-1050mA, 20-50V
8002699	PCA: LED Strip 5P8S, ALS-50-840-3-01-A

The product details described in this document are current as at the version date of the document. We reserve the right to change product design, specifications or materials (Specifications) as part of our continuous improvement program. Please confirm the applicable Specifications at the time of placing your order