



CLEVERTRONICS L10 OPTIMUM SURFACE MOUNT SWINGBLADE THEATRE LED EXIT



Standard mask – For height reference only



Theatre mask version – black body as standard

PRODUCT INFORMATION

Catalogue Number	LSBLED-TH-R
Description	LED L10 OPTIMUM Swingblade Theatre Exit, 24 metre viewing Distance
Construction	Black Metal Frame, Black End Caps with Acrylic Diffuser
Mounting	Surface Mount, Wall or Ceiling on a slide connect bracket – Single & Double Sided “NOTE: If product is suspended below the ceiling or mounted on a metal surface the Swingblade bracket cover plate accessory (P/N: 2740105) is required to cover the mains terminals.”
Dimensions L x W x H	See Images above
Operating Mode	Maintained
Testing System	Manual Test Switch
Charging Method	Intelligent current limited constant voltage charger
Diffuser	Theatre Mask (must specify diffuser combination)
Lamp(s)	24 x high intensity, low energy LED, surface mounted onto a replaceable lamp bar - 100,000hour
Operating Voltage	240V
Power Consumption	3.8W (standby) 5.8W (max during 16 hour charge)
IP Rating	IP20
Operating Temperature	1° to 40°C
AS/NZ2293 Classification	NA – Theatre Mask

REPLACEMENT PARTS

PART NUMBER	DESCRIPTION
1530070	Battery: 3.3Volt, 2.5Ah Li-ion
8002354	PCA:LBSLED-TH #CT10164-L4 6C20
8002185	PCA: 24DLED SB LED Strip, #CT10156-D2