

## CLEVERTRONICS L10 LIFELIGHT PRO RECESSED IP65 WEATHERPROOF EMERGENCY



### PRODUCT INFORMATION

Part Number	LLIFE-PRO-RECWP-WHT
Description	L10 Optimum LifeLight PRO, high performance, IP65 recessed Emergency Light with remote gear [IP20]
Construction	Die Cast Aluminium Body 316 Stainless Steel Screws Clear Toughened Glass
Mounting	Recessed Ceiling
Dimensions L x W x H	232mm x 40mm x 40mm (Control pack) 120mm head diameter
Ceiling Hole Cut-Out	106mm
Minimum Ceiling Depth	120mm
Operating Mode	Non-maintained
Testing System	Single Point Unit / Clevertest Plus [Activated on site]
Battery	Lithium Nanophosphate, 3.3V 5000mAh
Charging Method	Intelligent current limited constant voltage
Lamp(s)	Dual LED (Lifetime warranty on the lamp head and loom assembly)
Operating Voltage	240V AC; 50Hz
Power Consumption	0.4 Watts (Standby), 4.7 Watts (Max)
IP Rating	IP65 (Lamp head only)
Operating Temperature	0°C to 40°C
AS2293 Classification	C <sub>0</sub> =D40 C <sub>90</sub> =D40
Impact Rating	IK10

### REPLACEMENT PARTS

PART NUMBER	DESCRIPTION
1530230	BATTERY:L10 3.3V 5AH. 200mm lead.Brkt.
LLIFE-PRO-CKIT	Lifelight Pro, Control Only, LP/L10
1100830	Lifelight Pro Head Assembly, Round

