

CLEVERTRONICS LP LIFELIGHT PRO CYLINDER SURFACE MOUNT EMERGENCY



PRODUCT INFORMATION

Catalogue Number	CLIFE-PRO-SMC
MIC	AUT02310150001
Description	Lifelight PRO, High Performance, Cylinder Surface Mount Emergency Light with Lithium Battery Technology, Enabled with Clevertest Plus
Mounting	Surface Mount
Dimensions	128mm (D), 252mm (L)
Operating Mode	Non-Maintained
Testing System	Clevertest Plus Enabled (Not activated by default)
Ballast	N/A
Charging Method	Intelligent current limited constant voltage charger
Lamps(s)	2 x 3W LED (Lifetime warranty on the lamp head and loom assembly)
Operating Voltage	240V 50Hz
Power Consumption	0.4 Watts (Standby) 2.7 Watts (Max)
IP Rating	IP20
Operating Temperature	1° to 40°C (Ambient)
AS/NZ2293 Classification	C ₀ =D63 C ₉₀ =D63

REPLACEMENT PARTS

PART NUMBER	DESCRIPTION
1550230	Battery, LP 3.2V 6400mAh.200mm lead.Brkt.
1100838	Lifelight Pro Head Assembly, Ld:280mm,Round, Gen 2
AUM02370050001	LifelightPro,Control Only, 530mm, NP, CTP, OWC

The product details described in this document are current as at the version date of the document. We reserve the right to change product design, specifications or materials (Specifications) as part of our continuous improvement program. Please confirm the applicable Specifications at the time of placing your order