

CLEVERTRONICS LP LED SUPALITE



PRODUCT INFORMATION	
Catalogue Number	CFLLED-BLK
Description	LP Premium Supalite LED Flood Unit, Surface Mounted Emergency Light, Enabled with Clevertest Plus, Black
Construction	Polycarbonate
Mounting	Surface Mounted. Supplied with flex and plug (the flex and plug can be removed to allow for a hard wired connection)
Dimensions L x W x H	Main enclosure - 282mm (W) x 137mm (H) x 64mm (D) Total height including LED Heads 225mm.
Weight	1.3kg
Operating Mode	Non-maintained
Testing System	Clevertest Plus Enabled (Not activated by default)
Charging Method	Intelligent Current Limited Constant Voltage
Lamp(s)	2 x LED Heads (adjustable), 185lm per lamp head
Operating Voltage	240V AC; 50Hz
Power Consumption	0.4 Watts (Standby), 2.2 Watts (Max)
IP Rating	IP20
Operating Temperature	1°C to 40°C
AS2293 Classification	$C_0=N/A$ $C_{90}=N/A$

REPLACEMENT PARTS	
PART NUMBER	DESCRIPTION
1550230	BATT:LP 3.2V 6400mAh.200mm lead.Brkt.
8002390	PCA:LL-Pro L10 Driver 550mA .#CT10142-L5
1100955	LED Flood Lamp Head Ass, Cable & Cnnctr.




Version: April 2019-1






Spacing Guidance

Polar curve for a single LED lamp head





Isolux plot and value table for a 10m x 10m area serviced by an CFLLED with each LED lamp head tilted down 30°, rolled out 30°. CFLLED mounted on the wall at a height of 3m (values in lux).

