

Floodlight LED 10 W rechargeable AU/NZ



Benefits

- Long independent operating time for extended jobs.
- Compact design for minimal overall dimensions.
- Adjustable magnetic clamp compatible with tripod.

Norms

> IP 54

GENERAL INFORMATION

Description

Rechargeable 10 W LED spotlight

Technical details

Power : 10 W.
Luminous flux : 1100 lm (Mode : 100 %) or 400 lm (Mode : 50 %).
Color temperature : 6000 K.
Color rendering index : 80.
Beam angle : 120°.
Resistance to 1 m height drop.
Material : Aluminium and rubber.
Clamp adjustable to 180°.
Magnetic clamp compatible with tripod.
Independent operating time 3 h (mode : 100 %) or 6 h (mode : 50 %).
Charge time : 6 h.
Charge indicator.
Battery Lithium 3.7 V / 4400 mAh.
Charger input voltage : 100-240 V AC.
Charger output voltage : 5 V DC - 1 A.
Powerbank USB port.
Supplied with main charger and a connection cable length 1 meter.
Weight : 750 grams.

Advice

Fully charge and discharge the battery for better lifetime.

Application(s)

Temporary battery-powered site lighting.

Instructions

1. Button to choose the desired luminous flux (100 % - 50 % - Off). Operates when the device is connected to the mains.

LOGISTIC INFORMATION

Packaging



Hanging carton box

Height (cm) : 23.5
Length (cm) : 19.5
Depth (cm) : 5.5
Net weight (kg) : 0.86
Gross weight (kg) : 0.93



Outer package 1



Carton box

Height (cm) : 40
Length (cm) : 18
Depth (cm) : 24
Net weight (kg) : 5.5
Gross weight (kg) : 5.7

x 6.00



Outer package 2



Carton box

Height (cm) : 41.5
Length (cm) : 25.5
Depth (cm) : 38
Net weight (kg) : 11
Gross weight (kg) : 12

x 12.00



Outer package 3



Pallet

Height (cm) : 100
Length (cm) : 120
Depth (cm) : 80
Net weight (kg) : 252
Gross weight (kg) : 267

x 252.00

