

41E10PBSWM-VW

Switch 40 Series Module - Wiser - Push-button - ControlLink - 3-wire - 240 V - 10 AX - Vivid White



Main

Range	Clipsal Iconic
Product or component type	Electronic switch
Device presentation	Mechanism

Complementary

Device mounting	Flush
Actuator	Push-button
Fixing mode	Clip-in
Colour tint	Vivid white
Surface finish	Glossy
Type of packing	Box
Sale per indivisible quantity	1
Time delay	1...86400 s (24 h) adjustable
Remote control type	Push-button Wiser room application
[I _e] rated operational current	10 A
[U _e] rated operational voltage	220...240 V AC 50 Hz
Load type	LED lighting 10 A Incandescent lamp 10 A Low voltage halogen lamp with iron core transformer 10 A Low voltage halogen lamp with electronic transformer 10 A Fluorescent lamp 10 A Compact fluorescent lamp 10 A Resistive 15 A
Power range	> 0 W
Derating factor	1 devices 10 A without 2 devices 7.5 A with derating factor 3 devices 6.5 A with derating factor 4 devices with derating factor 5 devices with derating factor 6 devices with derating factor
Operating distance	30 m
Control signal type	ControlLink
Connections - terminals	Screw terminals
Number of terminals	4
Wiring configuration	3 wires with neutral
Screwdriver shape	Philips Square drive no 1 (SQ1)
Local signalling	LED indicator (warm white)
Material	PC (UL94 V-2): top PC MAS056 (UL94 V-2): bottom
Height	24 mm
Width	48 mm

Depth	56 mm
Embedding depth	52 mm
Standards	AS/NZS 60669.2.1

Environment

Ambient air temperature for storage	0...60 °C
Ambient air temperature for operation	0...45 °C
Relative humidity	0...90 %

Offer Sustainability

EU RoHS Directive	Compliant EU RoHS Declaration
Mercury free	Yes
RoHS exemption information	Yes
China RoHS Regulation	China RoHS Declaration