

## DISPLAY & LED FLEXI-STRIPS

VEGAS LED SINGLE COLOUR, RGB AND RGB+W FLEXI-STRIP WITH STANDARD OR WI-FI CONTROLLERS

# ROBUS®

NON-DIMMABLE DRIVERS										WALL SWITCH DIMMABLE DRIVERS		
12V	IP20	RVA3012-PSU	RVA6012-PSU	RVA10012-PSU	NA	RVA18012-PSU	NA	NA	NA	RVA3012DU-PSU	RVA5012DU-PSU	RVA7512DU-PSU
12V	IP67	NA	RVA6012IP67-PSU	RVA10012IP67-PSU	NA	NA	RVA20012IP67-PSU	NA	NA	NA	NA	NA
24V	IP20	RVA3024-PSU	RVA6024-PSU	RVA10024-PSU	RVA15024-PSU	NA	NA	RVA25024-PSU	RVA32024-PSU	RVA3024DU-PSU	RVA5024DU-PSU	RVA7524DU-PSU
24V	IP67	NA	RVA6024IP67-PSU	RVA10024IP67-PSU	NA	NA	RVA20024IP67-PSU	NA	NA	NA	NA	NA
<b>Total Power (W):</b>		30	60	100	150	180	200	250	320	30	50	75
<b>Rated Life (hrs):</b>		30,000	30,000	30,000	30,000	30,000	30,000	30,000	30,000	30,000	30,000	30,000
<b>Warranty (yrs):</b>		3	3	3	3	3	3	3	3	3	3	3
<b>Safety Class:</b>		II	II/I	II/I	II	II	I	II	II	II	II	II
<b>Operating Temp (°C):</b>		-20 ≤ t ≤ +40	-20 ≤ t ≤ +40	-20 ≤ t ≤ +40	-20 ≤ t ≤ +40	-20 ≤ t ≤ +40	-20 ≤ t ≤ +40	-20 ≤ t ≤ +40	-20 ≤ t ≤ +40	-20 ≤ t ≤ +40	-20 ≤ t ≤ +40	-20 ≤ t ≤ +40
<b>Power Factor (PF):</b>		0.9	0.9	0.9	0.9	0.9	0.9	0.9	0.9	0.9	0.9	0.9
<b>Height (mm):</b>		27	28/30	31/38	31	31	38	36	35	18	18	31
<b>Length (mm):</b>		149	170/216	180/212	180	183	212	195	215	158	158	170
<b>Width (mm):</b>		40	45/42	65/46	66	67	46	62	78	46	46	56
<b>Weight (kg):</b>		0.12	0.22/0.53	0.37/0.58	0.41	0.41	0.8	0.42	0.44	0.12	0.21	0.3

## AMPLIFIERS AND CONTROLLERS



\*\*\*-AMP



RVA4CH-REC with RVA4CH-RC



RVA\*\*\*\*-Wi-Fi

Product Code:	RVACCT1-AMP	RVARGB-AMP	RVARGBW-AMP	RVA4CH-REC	RVA4Z-RC	RVACCT1-WIFI	RVARGB-WIFI	RVARGBW-WIFI
<b>Total Power 12V/24V (W):</b>	144/288	216/432	384/768	288/576	NA	120/240	120/240	120/240
<b>Rated Life (hrs):</b>	30,000	30,000	30,000	30,000	30,000	30,000	30,000	30,000
<b>Warranty (yrs):</b>	3	3	3	3	3	3	3	3
<b>Ingress Protection (IP):</b>	20	20	20	20	20	20	20	20
<b>Operating Temperature (°C):</b>	-20 ≤ t ≤ +40							
<b>Output Current (mA):</b>	2x6,000	3x6,000	4x8,000	4x6,000	NA	1x10,000	3x5,000 (max 10A total)	4x5,000 (max 10A total)
<b>Operating Voltage (Vdc):</b>	12-24	12-24	12-24	12-24	NA	12-24	12-24	12-24
<b>Height Controller/Remote (mm):</b>	34	34	34	25	20	21	21	21
<b>Length Controller/Remote (mm):</b>	80	80	80	160	150	99	99	99
<b>Width Controller/Remote (mm):</b>	73	73	73	46	40	39	39	39
<b>Depth Controller/Remote (mm):</b>	NA	NA	NA	NA	NA	NA	NA	NA
<b>Box Qty:</b>	1	1	1	1	1	1	1	1
<b>Weight (kg):</b>	0.13	0.13	0.13	0.1	0.1	0.04	0.04	0.04

## ALUMINIUM EXTRUSIONS

Product Code	Description	Mounting Type	Strip Type	Profile
REXS082-23	Length 2m + 2 end caps	Surface	Single colour or RGB	1
REXS122-23	Length 2m + 2 end caps	Surface	Single, RGB & RGBW	2
REXR152-23	Length 2m + 2 end caps	Recessed	Single colour or RGB	3
REXR122-23	Length 2m + 2 end caps	Recessed	Single, RGB & RGBW	4
REXA172-23	Length 2m + 2 end caps	Surface	Single & RGB	5
REXA202-23	Length 2m + 2 end caps	Surface	Single, RGB & RGBW	6

