

90° TERMINATOR

Features & Benefits

- PVC 90 Degree Elbow Termination Fitting for CNM range Flexible PVC Conduit
- High performing chemical resistance and mechanical strength
- Manufactured to comply with AS 2053.1 and AS 2053.4 "Conduit systems for cable management"
- RoHS, WEEE compliant, UL listed variants available
- Manufactured from a Hi Tech hardened PVC, offering a general purpose non metallic conduit system particularly suitable for food and beverage applications due to the smooth exterior and smooth bore interior, inhibiting particle accumulation, offering excellent protection to wiring abrasion, sunlight, mild acids, alkaline and oils.



Ordering Information

PART NUMBER	DESCRIPTION
LT916P	Liquid Tight NM Fitting 90 Degrees 16mm
LT920P	Liquid Tight NM Fitting 90 Degrees 20mm
LT925P	Liquid Tight NM Fitting 90 Degrees 25mm
LT932P	Liquid Tight NM Fitting 90 Degrees 32mm
LT940P	Liquid Tight NM Fitting 90 Degrees 40mm
LT950P	Liquid Tight NM Fitting 90 Degrees 50mm

In support of our policy of continuous product improvement we reserve the right to change materials and specifications without notice. Drawings, where used, are not to scale. All dimensions are in millimetres and sizes given are approximate. Where possible, technical MSDS data sheets are made available on the website. All products should be installed and used in accordance with manufacturer's instructions provided. Warning: products may be the subject of registered designs and patents. Refer to website for terms and conditions on warranty.