

NON METALLIC LIQUID TIGHT CONDUIT

A general-purpose, non-metallic liquidtight conduit offers excellent protection to wiring from abrasion, sunlight, mild acids, alkaline and oils. Type CNM is a LNMHC helically wound integral Type B construction conduit, containing a spiral of rigid PVC reinforcement embedded with the PVC wall.




Features & Benefits

- Flexible spiral wound PVC conduit made from a Very Hard PVC Spiral encased in a PVC extrusion giving us a High Strength Smooth Bore Conduit
- UV stabilised black, green, grey, orange and blue PVC jacket Operating Temp of -20 to +80 deg Superior Chemical Resistance
- Suitable for Food Prep environments, Mining Applications, Water Treatment
- Machine Wiring and other Industrial Areas PVC fittings available but can also be used with CABFLX Steel Brass and Stainless Steel Fittings
- IP 66/68 when mated with suitable connectors which are also a hardened PVC.
- Manufactured to comply with AS 2053.1 and AS 20153.4 "Conduit systems for cable management." RoHS, WEEE complaint, UL listed variants also available



Line Drawing



Ordering Information

Part No.	Colour	Nominal Size (mm)	ID (mm)	OD (mm)	Min Inside Bend (mm)	Carton Reel Length (m)	Straight Fitting	90 Fitting
CNM16BK-30	Black	16	12.5	17.8	51	30	LT16P	LT916P
CNM20BK-30	Black	20	16	21.1	72.5	30	LT20P	LT920P
CNM25BK-30	Black	25	21	26.4	108	30	LT25P	LT925P
CNM32BK-30	Black	32	26.7	33.1	165	30	LT32P	LT932P
CNM40BK-10	Black	40	35.5	41.8	203	30	LT40P	LT940P
CNM50BK-10	Black	50	40.3	47.9	228.5	15	LT50P	LT950P
CNM63BK-10	Black	63	51.6	59.7	282	15	LT63P	LT963P
CNM16BL-30	Blue	16	12.5	17.8	51	30	LT16P	LT916P
CNM20BL-30	Blue	20	16	21.1	72.5	30	LT20P	LT920P
CNM25BL-30	Blue	25	21	26.4	108	30	LT25P	LT925P
CNM32BL-30	Blue	32	26.7	33.1	165	30	LT32P	LT932P
CNM16GN-30	Green	16	12.5	17.8	51	30	LT16P	LT916P
CNM20GN-30	Green	20	16	21.1	72.5	30	LT20P	LT920P
CNM25GN-30	Green	25	21	26.4	108	30	LT25P	LT925P
CNM32GN-30	Green	32	26.7	33.1	165	30	LT32P	LT932P
CNM16GR-30	Grey	16	12.5	17.8	51	30	LT16P	LT916P
CNM20GR-30	Grey	20	16	21.1	72.5	30	LT20P	LT920P
CNM25GR-30	Grey	25	21	26.4	108	30	LT25P	LT925P
CNM32GR-30	Grey	32	26.7	33.1	165	30	LT32P	LT932P
CNM16OR-30	Orange	16	12.5	17.8	51	30	LT16P	LT916P
CNM20OR-30	Orange	20	16	21.1	72.5	30	LT20P	LT920P
CNM25OR-30	Orange	25	21	26.4	108	30	LT25P	LT925P
CNM32OR-30	Orange	32	26.7	33.1	165	30	LT32P	LT932P

In support of our policy of continuous product improvement we reserve the right to change materials and specifications without notice. Drawings, where used, are not to scale. All dimensions are in millimetres and sizes given are approximate. Where possible, technical MSDS data sheets are made available on the website. All products should be installed and used in accordance with manufacturer's instructions provided. Warning: products may be the subject of registered designs and patents. Refer to website for terms and conditions on warranty.