

HD METAL GREY JACKET

Features & Benefits

- Heavy duty, flexible spiral wound conduit made from hot dipped galvanised steel with corrosion resistant core
- UV stabilised grey PVC jacket, superior chemical resistance
- Compression resistant to HD rating of 1250 Newtons
- Operating temperature -10 to +105 degrees Celsius, resistance to burning
- IP66 with CABFLX fittings



PART No.	NOMINAL SIZE (mm)	TRADE SIZE (inch)	ID (mm)	OD (mm)	MIN BEND RADIUS (mm)	LENGTH (m)
CLT16GR	16	¾	12.6	17.8	50	25
CLT20GR	20	½	16.1	21.1	65	25
CLT25GR	25	¾	21.0	26.5	75	25
CLT32GR	32	1	26.5	33.1	100	25
CLT40GR	40	1¼	35.1	41.8	120	10
CLT50GR	50	1	40.4	47.9	140	10
CLT63GR	63	2	51.6	59.9	180	10
CLT80GR	80	3	78.4	88.4	300	10

Ordering Information

PART No.	DESCRIPTION
CLT16GR	Liquid Tight Metal 16mm Grey 25m
CLT20GR	Liquid Tight Metal 20mm Grey 25m
CLT25GR	Liquid Tight Metal 25mm Grey 25m
CLT32GR	Liquid Tight Metal 32mm Grey 25m
CLT40GR	Liquid Tight Metal 40mm Grey 10m
CLT50GR	Liquid Tight Metal 50mm Grey 10m
CLT63GR	Liquid Tight Metal 63mm Grey 10m
CLT80GR	Liquid Tight Metal 80mm Grey 10m

In support of our policy of continuous product improvement we reserve the right to change materials and specifications without notice. Drawings, where used, are not to scale. All dimensions are in millimetres and sizes given are approximate. Where possible, technical MSDS data sheets are made available on the website. All products should be installed and used in accordance with manufacturer's instructions provided. Warning: products may be the subject of registered designs and patents. Refer to website for terms and conditions on warranty.