

HD STAINLESS STEEL BLACK JACKET

Features & Benefits

- Heavy duty, flexible 304 grade stainless steel conduit, spiral wound with corrosion resistant core
- UV stabilised black PVC jacket, superior chemical resistance
- Compression resistant to HD rating of 1250 Newtons
- Operating temperature -10 to +105 degrees Celsius, resistance to burning
- IP66 with CABFLX fittings



Ordering Information

PART NUMBER	NOMINAL SIZE (MM)	TRADE SIZE (INCH)	ID (MM)	OD (MM)	MIN BEND RADIUS (MM)	LENGTH (M)
CSS16BK	16	3/8	12.6	17.8	50	25
CSS20BK	20	1/2	16.1	21.1	65	25
CSS25BK	25	3/4	21.0	26.5	75	25
CSS32BK	32	1	26.5	33.1	100	25
CSS40BK	40	1-1/4	35.1	41.8	120	10
CSS50BK	50	1-1/2	40.4	47.9	140	10
CSS63BK	63	2	51.6	59.9	180	10

In support of our policy of continuous product improvement we reserve the right to change materials and specifications without notice. Drawings, where used, are not to scale. All dimensions are in millimetres and sizes given are approximate. Where possible, technical MSDS data sheets are made available on the website. All products should be installed and used in accordance with manufacturer's instructions provided. Warning: products may be the subject of registered designs and patents. Refer to website for terms and conditions on warranty.