



STRAIGHT STEEL FITTING

Features & Benefits

- Zinc plated steel Liquid Tight straight configuration, presents a male thread
- Tested and Certified to IEC60079-0: 2007-10 and IEC60079-31: 2008
- Ex ta IIIC IP66, IEC Ex TSA 11.0026
- High performing chemical resistance and mechanical strength
- Supplied with a flanged grounding cone and sealing ring



Line Drawing



PART NO.	THREAD SIZE (MM)	CONDUIT SIZE (MM)	A (MM)	B (MM)	C HEX MAX (MM)
LTCM-09	16	16	23	12.7	28
LTCM-10	20	16	23	12.7	28
LTCM-11	20	20	23	12.7	31.5
LTCM-12	25	25	26	14.2	38.5
LTCM-13	32	32	28	16.3	46.5
LTCM-14	40	40	33	18.2	59
LTCM-15	50	50	32	18.2	67
LTCM-16	63	63	34	20	80

Ordering Information

PART NUMBER	DESCRIPTION
LTCM-09	Liquid tight Straight Metal Fitting 16mm
LTCM-10	Liquid tight Straight Metal Fitting 16/20mm
LTCM-11	Liquid tight Straight Metal Fitting 20mm
LTCM-12	Liquid tight Straight Metal Fitting 25mm
LTCM-13	Liquid tight Straight Metal Fitting 32mm
LTCM-14	Liquid tight Straight Metal Fitting 40mm
LTCM-15	Liquid tight Straight Metal Fitting 50mm
LTCM-16	Liquid tight Straight Metal Fitting 63mm

In support of our policy of continuous product improvement we reserve the right to change materials and specifications without notice. Drawings, where used, are not to scale. All dimensions are in millimetres and sizes given are approximate. Where possible, technical MSDS data sheets are made available on the website. All products should be installed and used in accordance with manufacturer's instructions provided. Warning: products may be the subject of registered designs and patents. Refer to website for terms and conditions on warranty.