


STAINLESS STEEL 90 DEGREE FITTING

Features & Benefits

- 304 grade stainless steel Liquid Tight 90 degree fitting, presents a male thread
- Tested and Certified to IEC60079-0: 2007-10 and IEC60079-31: 2008
- Ex ta IIIC IP66, IEC Ex TSA 11.0026
- High performing corrosion and chemical resistance, high mechanical strength
- Supplied with a flanged grounding cone and sealing ring



Line Drawing



PART NO.	THREAD SIZE (MM)	CONDUIT SIZE (MM)	A (MM)	B A/C (MM)	C A/C (MM)	D (MM)
LTCM-S20	20	16	56	32	28	36
LTCM-S21	20	20	56	32	31.5	38
LTCM-S22	25	25	63	39	38.5	46
LTCM-S23	32	32	80	45	46.5	55
LTCM-S24	40	40	98	58	59	70
LTCM-S25	50	50	97	65	67	73
LTCM-S26	63	63	117	80	80	88

Ordering Information

PART NUMBER	DESCRIPTION
LTCM-S20	Liquid Tight 90 Degree Stainless Steel Fitting 16/20mm
LTCM-S21	Liquid Tight 90 Degree Stainless Steel Fitting 20mm
LTCM-S22	Liquid Tight 90 Degree Stainless Steel Fitting 25mm
LTCM-S23	Liquid Tight 90 Degree Stainless Steel Fitting 32mm
LTCM-S24	Liquid Tight 90 Degree Stainless Steel Fitting 40mm
LTCM-S25	Liquid Tight 90 Degree Stainless Steel Fitting 50mm
LTCM-S26	Liquid Tight 90 Degree Stainless Steel Fitting 63mm

In support of our policy of continuous product improvement we reserve the right to change materials and specifications without notice. Drawings, where used, are not to scale. All dimensions are in millimetres and sizes given are approximate. Where possible, technical MSDS data sheets are made available on the website. All products should be installed and used in accordance with manufacturer's instructions provided. Warning: products may be the subject of registered designs and patents. Refer to website for terms and conditions on warranty.