

HD METAL BLACK JACKET

Features & Benefits

- Heavy duty, flexible spiral wound conduit made from hot dipped galvanised steel with corrosion resistant core
- UV stabilised black PVC jacket, superior chemical resistance, IP66 with CABFLX fittings
- Compression resistant to HD rating of 1250 Newtons
- Operating temperature -10 to +105 degrees Celsius, resistance to burning
- Custom Cut Lengths Pre-Terminated on request MOQ's Apply



Technical Data

PART No.	NOMINAL SIZE (mm)	TRADE SIZE (inch)	ID (mm)	OD (mm)	MIN BEND RADIUS (mm)	LENGTH (m)
CLT16BK	16	¾	12.6	17.8	50	25
CLT20BK-10	20	½	16.1	21.1	65	10
CLT20BK	20	½	16.1	21.1	65	25
CLT20BK-50	20	½	16.1	21.1	65	50
CLT25BK-10	25	¾	21.0	26.5	75	10
CLT25BK	25	¾	21.0	26.5	75	25
CLT25BK-150	25	¾	21.0	26.5	75	150
CLT32BK-10	32	1	26.5	33.1	100	10
CLT32BK	32	1	26.5	33.1	100	25
CLT40BK	40	1½	35.1	41.8	120	10
CLT50BK	50	1½	40.4	47.9	140	10
CLT63BK	63	2	51.6	59.9	180	10
CLT80BK	80	3	78.4	88.4	300	10
CLT100BK	100	4	102.1	113.8	350	10

Ordering Information

PART No.	DESCRIPTION
CLT16BK	Liquid Tight Metal 16mm Black 25M
CLT20BK-10	Liquid Tight Metal 20mm Black 10M
CLT20BK	Liquid Tight Metal 20mm Black 25M
CLT20BK-50	Liquid Tight Metal 20mm Black 50M
CLT25BK-10	Liquid Tight Metal 25mm Black 10M
CLT25BK	Liquid Tight Metal 25mm Black 25M
CLT25BK-150	Liquid Tight Metal 25mm Black 150M
CLT32BK-10	Liquid Tight Metal 32mm Black 10M
CLT32BK	Liquid Tight Metal 32mm Black 25M
CLT40BK	Liquid Tight Metal 40mm Black 10M
CLT50BK	Liquid Tight Metal 50mm Black 10M
CLT63BK	Liquid Tight Metal 63mm Black 10M
CLT80BK	Liquid Tight Metal 80mm Black 10M
CLT100BK	Liquid Tight Metal 100mm Black 10M

In support of our policy of continuous product improvement we reserve the right to change materials and specifications without notice. Drawings, where used, are not to scale. All dimensions are in millimetres and sizes given are approximate. Where possible, technical MSDS data sheets are made available on the website. All products should be installed and used in accordance with manufacturer's instructions provided. Warning: products may be the subject of registered designs and patents. Refer to website for terms and conditions on warranty.