

ECO LED Panel Gen2

ECOPL1234EG2

- One box solution 3-in-1 Colour Select option to choose the right colour temperature for the application
- Easy to install Remote constant current driver with 1.2 meter flex and plug and light-weight design
- Quality opal diffuser delivering high quality and even light distribution



Performance

System Power	27W
Exit Lumen	2900lm
Lm/W	107lm/W
CCT	4000K
CRI	80
Operating Temperature	0 - 40°C
MacAdam Steps	6SDCM
Ingress Protection Rating	IP40
Beam Distribution	Symmetric
Beam Angle	110°
Warranty	3 Years
Lifetime	105,000hrs (L80/10)


Physical

1 Hydrodi	
Dimensions	L1195 x W295 x H30mm
Diffuser	Polystyrene
Luminaire Colour	White
Weight	2kg
Luminaire Material	Aluminium (Extruded)
Driver Location	Remote
Finish	Powder Coated
Installation	Recessed

Electrical

Dimming	Non - Dimmable
Voltage	240V
Line Voltage Frequency	50Hz
Inrush Current	2A
Inrush Current Duration	52µs
Line Current	0.12A
Electrical Rating	Class II

Line Drawings



Product Images





Accessories

ECOPLWIREKITG2	BACKLIT PANEL SUSPENSION KIT 1M Y- SHAPE WIRE 2 BRACKETS
UDFRM/12-3	Universal Deep Frame 1200x300mm
UDFRM/12-6	Universal Deep Frame 1200x600
UDFRM/6-3	Universal Deep Frame 600x300mm
UDFRM/6-6	Universal Deep Frame 600x600
FRM/PM18W	Plaster frame to mount in plaster ceiling - White, 600x300mm
FRM/PM18WIDE	Plaster frame to mount in plaster ceiling - White, 600x600mm
FRM/PM36W	Plaster frame to mount in plaster ceiling - White, 1200x300mm
FRM/PM126L	1200X600 LOCAL PL 36MM T FRAME / MASTER ASSY
ECOPNLBRKTKIT	
FRM/PM36WIDE	Plaster frame to mount in plaster ceiling - White, 1200x600mm