


## ECO LED Panel Gen2

### ECOPL1234UG19

- Easy to install - Remote constant current driver with 1.2 meter flex and plug and light-weight design
- Quality prismatic diffuser - delivering uniform and low glare illumination



#### Performance

System Power	34W
Exit Lumen	3200lm
Lm/W	94lm/W
CCT	4000K
CRI	80
Operating Temperature	0 - 40°C
UGR Design	19
MacAdam Steps	6SDCM
Ingress Protection Rating	IP40
Beam Distribution	Symmetric
Beam Angle	90°
Warranty	3 Years
Lifetime	105,000hrs (L80/B10)


#### Physical

Dimensions	L1195 x W295 x H30mm
Diffuser	Polystyrene
Luminaire Colour	White
Weight	2kg
Luminaire Material	Aluminium (Extruded)
Driver Location	Remote
Finish	Powder Coated
Installation	Recessed

#### Electrical

Dimming	Non - Dimmable
Voltage	240V
Line Voltage Frequency	50Hz
Inrush Current	2A
Inrush Current Duration	56µs
Line Current	0.15A
Electrical Rating	Class II

#### Line Drawings



#### Product Images



## Accessories

ECOPLWIREKITG2	BACKLIT PANEL SUSPENSION KIT 1M Y-SHAPE WIRE 2 BRACKETS
UDFRM/12-3	Universal Deep Frame 1200x300mm
UDFRM/12-6	Universal Deep Frame 1200x600
UDFRM/6-3	Universal Deep Frame 600x300mm
UDFRM/6-6	Universal Deep Frame 600x600
FRM/PM18W	Plaster frame to mount in plaster ceiling - White, 600x300mm
FRM/PM18WIDE	Plaster frame to mount in plaster ceiling - White, 600x600mm
FRM/PM36W	Plaster frame to mount in plaster ceiling - White, 1200x300mm
FRM/PM126L	1200X600 LOCAL PL 36MM T FRAME / MASTER ASSY
ECOPNLBRKTKIT	
FRM/PM36WIDE	Plaster frame to mount in plaster ceiling - White, 1200x600mm