

SOLAR-400-TRIO Ceiling Light



Description

The SOLAR-RND range of surface mounted LED ceiling lights feature a simple, round and unobtrusive design while providing a 120° beam of uniform light-output through the use of high intensity SMDs (Surface Mounted Diodes).

The SOLAR-RND is constructed from polycarbonate and rated at IP54, making it ideal for usage in damp locations and in dwellings located close to coastal areas.

SOLAR-RND LED ceiling lights are available now with TRIO, the added option of changing the colour temperature output of the downlight with a dip switch at the back of the fitting. All models come complete with driver, (fully dimmable with suitable dimmers) have a lifetime of 40,000 hours and are backed by our Three Year Replacement Warranty.



Specification Features

- Input Voltage: AC 240V
 - Power (W): 35W
 - IP rating (IP): IP54
 - Lumens (lm): Warm White 3000K - 3000lm
Neutral White 4000K - 3050lm
White 5700K - 3100lm
 - LED type: SMD
 - CCT: 3000K - 4000K -5700K (Switchable)
 - CRI: ≥80
 - Beam angle (°): 120°
 - Dimmable: Yes**
 - Lifespan (hrs): 40,000hrs
- ** Tested on the Domus Dimmer Series. May work on others but not tested.



Diagrams / Additional



Item No.	Variant	Colour
SOLAR-RND-400-TRIO	20942	White
	20943	Black