

# **PRODUCT DATASHEET**MS-SV INF-CR-A 360 220-240 V IP20

**LED VALUE PIR Motion Sensor | Sensors with infrared technology** 



# **AREAS OF APPLICATION**

- Suitable for indoor applications
- Offices
- Corridors
- Stairways
- Residential interiors
- Commercial buildings

#### **PRODUCT FEATURES**

- 360° motion sensor (passive infrared technology)
- Ceiling surface and recessed mounting
- Timer function
- Adjustable illuminance from 3 or 10 lx to 2000 lx via knob switch (model dependent)
- Photocell detector available for daylight detection
- Input voltage: 220...240 V<sub>AC</sub>
- Operating frequency: 50/60 Hz
- Ambient temperature in operation: -20...+40 °C
- Type of protection: IP20

# **TECHNICAL DATA**

# Electrical data

Nominal voltage	220240 V
-----------------	----------

#### Luminaire sensor data

Sensor technology	Passive infrared/Photocell

# Dimensions & weight

Width	80.0 mm
Height	62.0 mm
Product weight	69.30 g

#### Colors & materials

Product color	White

# Temperatures & operating conditions

Ambient temperature range	-20+40 °C
•	

# Capabilities

Detection angle	360 °
Detection area	8 m²
Maximum installation height	2.24 m

# Light management & control

# Certificates & standards

Protection class	Ш
Type of protection	IP20

# LOGISTICAL DATA

Product code	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Gross weight	Volume
4058075373013	Folding carton box 1	85 mm x 64 mm x 96 mm	93.00 g	0.52 dm <sup>3</sup>
4058075373020	Shipping carton box 10	332 mm x 182 mm x 116 mm	1105.00 g	7.01 dm <sup>3</sup>

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

# **DISCLAIMER**

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.