

ET-PARROT 70/220...240 I

ET-PARROT | Electronic transformers for low-voltage halogen lamps



Product family features

- Line frequency: 50...60 Hz
- RI suppression: to EN 55015 (A1: 2007)/CISPR 15, EN 55022
- Line harmonics according to EN 61000-3-2
- Immunity according to EN 61547
- Safety: to EN 61347
- Short-circuit protection, overload protection, overtemperature protection: electronically reversible
- Electrical isolation between the primary side and the secondary side
- Dimmable on the leading edge and trailing edge

Product family benefits

- Very low power loss thanks to high efficacy
- Protective operation throughout the entire partial-load range for long lamp life

Areas of application

- Effect and accent lighting
- Living rooms
- Object lighting
- Conference rooms
- Restaurants
- Recessed and surface-mounted furniture luminaires
- Shop lighting
- Event rooms

Product datasheet

Technical data

Electrical data

Lamp wattage	20...70 W
Maximum output power	70 W
Line current	0.30 A ¹⁾
Nominal voltage	220...240 V
Power factor λ	0.95 ²⁾
Operating frequency	50 kHz ³⁾
Nominal output voltage	11.9 / 12.0 V ⁴⁾
Input voltage AC	198...264 V
Mains frequency	50...60 Hz
System wattage	74.00 W
Input voltage range	220...240 V
Max. ECG no. on circuit breaker 10 A (B)	37
Max. ECG no. on circuit breaker 16 A (B)	59
Efficiency in full-load	94 %
Galvanic isolation primary/secondary	4.00 kV ⁵⁾
Inrush current	0.45 A

1) Effectively


2) Minimum

3) Approximately

4) 70 W / 20 W

5) ϵ_{eff}

Dimensions & weight



Length	128.0 mm
Width	38.0 mm
Height	31.0 mm
Mounting hole spacing, length	119.0 mm

Product datasheet

Cable cross-section, input side	0.75 mm ²
Cable cross-section, output side	0.75 mm ²
Wire preparation length, input side	12 / 6.0 mm ¹⁾
Wire preparation length, output side	12 / 6.0 mm ¹⁾
Product weight	115.00 g

¹⁾ Cable sheath / Wire

Temperatures & operating conditions

Ambient temperature range	0...+45 °C
Maximum temperature at tc test point	70 °C

Additional product data

Design / version	Compact
------------------	---------

Capabilities

Dimming method	Trailing- or leading-edge phase control for inductive load dimmers
Overload protection	Automatic reversible
Overheating protection	Automatic reversible
Short-circuit protection	Automatic reversible
Max. cable length to lamp/LED module	2.0 m
Cable/wire types, input side	H03VV-F 2x0.75 mm ²
Cable/wire types, output side	H03VV-F 2x0.75 mm ²
Dimmable	Yes
Dimming range	0...100 %
No-load proof	Yes
Suitable for fixtures with prot. class	II
Intended for no-load operation	No

Certificates & standards







Approval marks – approval	VDE / EAC
Standards	Acc. to EN 61347/Acc. to EN 55015/Acc. to EN 61000-3-2/Acc. to EN 61547
Type of protection	IP20

Logistical data

Commodity code	850440909000
----------------	--------------

Product datasheet

Download Data

File	
	User instruction EAC - ET-PARROT ET-ZE
	Product Datasheet 321724_ATI ET-PARROT 105220-240 I ATI ET-PARROT 70220-240 I (G+GB)
	Certificates 504206_VDE-EMC-Certificate ET-PARROT
	Certificates 504178_EAC HT family
	Declarations of conformity HALTORONIC CE 3674444 210120
	CAD data 343999_ET-PARROT FILE STP

Logistical Data

Product code	Product description	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Volume	Gross weight
4008321111593	ET-PARROT 70/220...240 I	Shipping carton box 50	290 mm x 231 mm x 220 mm	14.74 dm ³	6221.25 g

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

Disclaimer

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.