



Discrete Distribution Module Panel, SL, Cat 6A, STP, 1U, 24 port

Product Classification

Portfolio	CommScope®
Product Type	RJ45 patch panel
Regional Availability	Australia/New Zealand

Dimensions

Depth, with cable management	119.38 mm 4.70 in
Diameter Over Dielectric, maximum	1.168 mm 0.046 in
Diameter Over Dielectric, minimum	0.762 mm 0.030 in
Height	44.45 mm 1.75 in
Width	482.60 mm 19.00 in

Electrical Specifications

ANSI/TIA Category	6A
--------------------------	----

Environmental Specifications

Flammability Rating	UL 94 V-0
Operating Temperature	-10 °C to +60 °C (+14 °F to +140 °F)
Safety Standard	cUL RCM UL
Storage Temperature	-40 °C to +70 °C (-40 °F to +158 °F)

General Specifications

Total Ports, quantity	24
Cable Type	Shielded
Color	Black
Growth Configuration	Fully loaded
Includes	Modular jacks (24)
Package Quantity	1
Rack Type	EIA 19 in
Rack Units	1.0

Mechanical Specifications

Panel Style Straight
Material Type High-impact, flame retardant, thermoplastic | Powder-coated steel

Regulatory Compliance/Certifications

Agency	Classification
RoHS 2011/65/EU	Compliant
ISO 9001:2015	Designed, manufactured and/or distributed under this quality management system

