

# Technical Specifications

Code	Occupancy	Width	Height	Depth	Panel Size
MEV121	1 Tenancy	470mm	670mm	275mm	400mm x 380mm
MEV121-150	1 Tenancy	470mm	670mm	350mm	400mm x 380mm
Code	Accessory	Width	Height	Depth	Fittings Supplied
TBKT-MEV1	Temp. Bracket	-	1.2m	-	Up to ø60mm Pipe
PLV1-65	Plinth	470mm	650mm	250mm	M8 x 20mm (4 off)
PLV1-100	Plinth	470mm	1000mm	250mm	M8 x 20mm (4 off)
RHS4	Rain Hood	470mm	45mm	335mm	M6 x 20 (4 off)

## MEV121 Features & Benefits

Suitable for up to 2 x Single Phase meters or 1 x Multi Phase meter (Single Occupancy)

Compliant with Victorian Service and Installation Rules (VESI Acceptance Number SIR140216B)

IP23 Rated meter enclosure

75mm Behind Meter Panel (Also available MEV121-150 with 150mm Behind Meter Panel)

Galvanised steel construction Powder Coated Light Grey (RAL7035)

Designed to AS/NZS 3000:2018 requirements

21 Module full DIN

400mm x 380mm pre-drilled double hinged Meter Panel

Metering Neutral Link 1 x 16mm<sup>2</sup> / 1 x 25mm<sup>2</sup> / 1 x 70mm<sup>2</sup>

Hand Operated Service Fuse Holder (22mm Fuse Link Diameter) Suitable for up to 100A / 35mm<sup>2</sup> Supply

Door open catch / Door cable protector / Equipped with CL001 fuse lock protection

Door open strap for easy installation & maintenance

### Earth & Neutral Bar Assembly

- 1 x 35mm<sup>2</sup> / 11 x 10mm<sup>2</sup> EARTH
- 4 x 25mm<sup>2</sup> / 4 x 10mm<sup>2</sup> NEUTRAL
- 2 x 35mm<sup>2</sup> / 7 x 10mm<sup>2</sup> RCD NEUTRAL
- 1 x 35mm<sup>2</sup> / 6 x 10mm<sup>2</sup> RCD NEUTRAL