



### Main

Range	Pro Series
Product or component type	Switch
Quantity per set	Set of 20

### Complementary

Device presentation	Mechanism
Control type	Rocker
Switch function	2-pole 1-way
Rated current	10 A
[Ue] rated operational voltage	250 V
Material	PC (polycarbonate) PA66 ABS (acrylonitrile butadiene-styrene)
Fixing mode	By clips
Connections - terminals	Screw terminal
Clamping connection capacity	1 x 1.5...4 x 1.5 mm <sup>2</sup> for rigid or stranded cable(s) 3 x 2.5 mm <sup>2</sup> for stranded cable(s) 1 x 4 mm <sup>2</sup> for stranded cable(s)
Height	23 mm
Width	23 mm
Depth	33 mm
Net weight	0.016 kg

### Environment

Ambient air temperature for operation	0...45 °C
Relative humidity	10...95 %
Product certifications	RCM

### Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Weight	16.98 g
Package 1 Height	2.2 cm
Package 1 width	2.2 cm
Package 1 Length	2.4 cm
Unit Type of Package 2	CAR
Number of Units in Package 2	160
Package 2 Weight	3.559 kg
Package 2 Height	23.0 cm
Package 2 width	26.7 cm

Package 2 Length	34.1 cm
Unit Type of Package 3	BB1
Number of Units in Package 3	20
Package 3 Weight	0.394 kg
Package 3 Height	16.7 cm
Package 3 width	10.5 cm
Package 3 Length	13.0 cm