# Product data sheet Characteristics

## A9MEM3250-NMI

## iEM3250 energy meter - CT - Modbus - NMI

#### Main

Range	Acti 9
Range of product	Acti 9 iEM3000
Device short name	iEM3250
Product or component type	Energy meter

#### Complementary

r		
Poles description	3P	
	3P + N 1P + N	
Type of measurement	Active energy	
	Current Voltage	
	Active power	
Device application	Sub billing	
Device application	Partial meter	
Accuracy class	Class 0.5S active energy conforming to IEC 62053-22	
ricouracy class	Class 0.5S active energy conforming to IEC 61557-12	
	Class C active energy conforming to EN 50470-3	
Input type	External CT 1 A or 5 A	
[In] rated current	5 A	
	1 A	
Rated voltage	100277 V	
	173480 V	
Network frequency	50 Hz	
	60 Hz	
Technology type	Electronic	
Display type	LCD display	
Sampling rate	32 samples/cycle	
Measurement current	132767000 mA	
Maximum value measured	99999999 MWh	
Communication port protocol	Modbus RTU at 9.6, 19.2 and 38.4 kbauds even/odd or none, insulation 4000 V	
Communication port support	Screw terminal block: RS485	
Local signalling	Green indicator light: power ON	
	Yellow flashing LED: accuracy checking	
	Yellow indicator light: communications are active on the Modbus port (Modbus)	
Number of inputs	0	
Number of outputs	0	
Mounting mode	Clip-on	
Mounting support	DIN rail	
Connections - terminals	Current circuit: screw terminals 6 mm² cable(s)	
	Voltage circuit: screw terminals 2.5 mm² cable(s)	
Overvoltage category	III	
	Voltage circuit: screw terminals 2.5 mm² cable(s)	

Standards	IEC 61557-12	
	IEC 62053-22	
	IEC 61036	
	IEC 62053-23	
	IEC 61010	
Product certifications	CE conforming to IEC 61010 (safety)	
	CE conforming to EN 61557-12 (power monitor)	
	CE conforming to IEC 61326-1 (EMC)	
	CULus conforming to UL 61010 (safety)	
	CULus conforming to ANSI C12.20 (sub-meter)	
	EAC (sub-meter)	
	RCM	
	ACMA	
	NMI conforming to NMI M 6-1 (sub-meter)	

#### Environment

IP degree of protection	IP40 front panel: conforming to IEC 60529 IP20 body: conforming to IEC 60529	
Pollution degree	2	
Relative humidity	595 % at 50 °C	
Ambient air temperature for operation	-2555 °C - IEC	
Ambient air temperature for storage	-4085 °C	
Operating altitude	< 2000 m	
Colour	White	
9 mm pitches	10	
Width	90 mm	
Height	95 mm	
Depth	69 mm	

### Packing Units

•		
Unit Type of Package 1	PCE	
Number of Units in Package 1	1	
Package 1 Weight	0.346 kg	
Package 1 Height	8.7 cm	
Package 1 width	9.5 cm	
Package 1 Length	10.5 cm	