Disclaimer. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability or these products for specific user applications



rack, Modicon X80, 10 slots, Redundant PS, Ethernet backplane, ruggedized

BMEXBP1002H

Main

Range of product	Modicon X80	
Accessory / separate part type	Ruggedized rack	
Product specific application	For severe environments	

Complementary

complementally		
Number of slots	8 bus X + Ethernet 2 bus X	
Product compatibility	Specific application module	
	BMX processor	
	BMXCPS4002	
	BME processor	
	I/O module	
Power consumption in W	251 mW 3.3 V DC	
	3.9 W 24 V DC	
Electrical connection	1 connector (XBE) expansion module	
Fixing mode	By 4 M6 screws, mounting on plate	
	By 4 screws - diameter: 4.326.35 mm, mounting on panel	
Current consumption	162 mA at 24 V DC	
	76 mA at 3.3 V DC	
MTBF reliability	1184170 H	
Net weight	1.37 kg	

Environment

IP degree of protection	IP20	
Ambient air temperature for operation	-2570 °C	
Relative humidity	595 % without condensation	
Directives	2014/35/EU - low voltage directive 2014/30/EU - electromagnetic compatibility 2014/34/EU - ATEX directive	
Product certifications	CE UL CSA RCM EAC Merchant Navy ATEX zone 2/22 IECEx zone 2/22	

Standards	IEC 61131-2	
	IEC 61010-2-201	
	UL 61010-2-201	
	CSA C22.2 No 61010-2-201	
	IACS E10	
	IEC 61000-6-5, interface type 1 and type 2	
	IEC 61850-3, location G	
	IEC 60079-0	
Environmental characteristic	Gas resistant class Gx conforming to ISA S71.04	
	Gas resistant class 3C4 conforming to IEC 60721-3-3	
	Dust resistant class 3S4 conforming to IEC 60721-3-3	
	Sand resistant class 3S4 conforming to IEC 60721-3-3	
	Salt resistant level 2 conforming to IEC 68252	
	Mold growth resistant class 3B2 conforming to IEC 60721-3-3	
	Fungal spore resistant class 3B2 conforming to IEC 60721-3-3	
	Hazardous location class I division 2	
Protective treatment	t Conformal coating	

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	6.500 cm
Package 1 Width	15.000 cm
Package 1 Length	58.500 cm
Package 1 Weight	1.369 kg
Unit Type of Package 2	S04
Number of Units in Package 2	8
Package 2 Height	30.000 cm
Package 2 Width	40.000 cm
Package 2 Length	60.000 cm
Package 2 Weight	11.520 kg



Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing "Use Better, Use Longer, Use Again" campaign to extend product lifetimes and recyclability.

Environmental Data explained >

How we assess product sustainability >

☑ Environmental footprint	
Carbon footprint (kg.eq.CO2 per CR, Total Life cycle)	214
Environmental Disclosure	Product Environmental Profile

Use Better

Materials and Substances	
Packaging made with recycled cardboard	Yes
Packaging without single use plastic	No
EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope)
REACh Regulation	REACh Declaration


Use Again

○ Repack and remanufacture	
Circularity Profile	End of Life Information
Take-back	No
WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins

BMEXBP1002H

Dimensions Drawings

Dimensions



Dimensions in mm

а			
Empty Rack	Rack With Extender Module Mounted	b	
506.20		NOTE: Overall height is 134.6 with a CPU mounted.	19

Dimensions in in.


а			
Empty Rack	Rack With Extender Module Mounted	b	С
19.93		NOTE: Overall height is 5.30 with a CPU mounted.	0.75

BMEXBP1002H

Mounting and Clearance

Minimum Clearance


Minimum Clearance of a typical installation in a cabinet with ducts



- a Side clearance: > 40 mm (1.57 in.)
- **b** Top and bottom clearance with surrounding objects: > 20 mm (0.79 in.)
- 1 Installation or casing
- 2 Wiring duct or tray

9 Apr 2025

Mounting and Fastening the Rack on Panels



NOTE: You can use M4, M5, M6, or UNC #6 screws in the fastening holes.


Dimensions in mm

а	b
462.90	475.60

Dimensions in in

a b		
18.22	18.72	

Mounting on Telequick Grid AM1-PA and AM3-PA Mounting Grids



Fasten the rack with four M4, M5, M6 or UNC #6 screws