Product datasheet

Specifications



Discrete output module, Modicon X80, 8 NO relay outputs, 24 to 240V AC / 24 to 125V DC, for severe environments

BMXDRA0815H

Main

Range of product	Modicon X80
Product or component type	Relay discrete output module
Product specific application	For severe environments
Discrete output number	8 conforming to EN/IEC 61131-2
Discrete output logic	Positive
Discrete output voltage	24240 V 19264 V AC 24125 V 5150 V DC

Complementary

Electrical connection	20 ways terminal block
Network frequency	50/60 Hz
Network frequency limits	4763 Hz
Sensor power supply	5150 V 19264 V
[Ith] conventional free air thermal current	3 A
Insulation resistance	> 10 MOhm 500 V DC
Power dissipation in W	3.6 W
Response time on output	<= 10 ms activation <= 13 ms deactivation
Typical current consumption	40 mA at 3.3 V DC 101 mA at 24 V DC
MTBF reliability	3200000 H
Protection type	External short-circuit protection External overload protection External overvoltage protection, inductive AC network External overvoltage protection, inductive DC network
Output overload protection	Use 1 fast blow fuse per channel or group of channel
Output overvoltage protection	Use discharge diode on each output DC Use RC circuit on each output AC Use ZNO surge limiter on each output AC
Output short-circuit protection	Use 1 fast blow fuse per channel or group of channel
Minimum switching current	1 mA 5 V DC

AC-12: 200000 cycles at 48 VA 24 V at -25...60 °C AC-12: 200000 cycles at 28.8 VA 24 V at 70 °C AC-12: 300000 cycles at 48 VA 48 V at -25...60 °C AC-12: 300000 cycles at 28.8 VA 48 V at 70 °C AC-12: 150000 cycles at 96 VA 48 V at -25...60 °C AC-12: 150000 cycles at 57.6 VA 48 V at 70 °C AC-12: 300000 cycles at 110 VA 100...120 V at -25...60 °C AC-12: 300000 cycles at 66 VA 100...120 V at 70 °C AC-12: 150000 cycles at 220 VA 100...120 V at -25...60 °C AC-12: 150000 cycles at 132 VA 100...120 V at 70 °C AC-12: 300000 cycles at 220 VA 200...250 V at -25...60 °C AC-12: 300000 cycles at 132 VA 200...250 V at 70 °C AC-12: 150000 cycles at 500 VA 200...250 V at -25...60 °C AC-12: 150000 cycles at 300 VA 200...250 V at 70 °C AC-15: 700000 cycles at 10 VA 24 V at -25...60 °C (load factor 0.4) AC-15: 700000 cycles at 6 VA 24 V at 70 °C (load factor 0.4) AC-15: 500000 cycles at 24 VA 24 V at -25...60 °C (load factor 0.4) AC-15: 500000 cycles at 14.4 VA 24 V at 70 °C (load factor 0.4) AC-15: 200000 cycles at 48 VA 24 V at -25...60 °C (load factor 0.4) AC-15: 200000 cycles at 28.8 VA 24 V at 70 °C (load factor 0.4) AC-15: 700000 cycles at 10 VA 48 V at -25...60 °C (load factor 0.4) AC-15: 700000 cycles at 6 VA 48 V at 70 °C (load factor 0.4) AC-15: 500000 cycles at 24 VA 48 V at -25...60 °C (load factor 0.4) AC-15: 500000 cycles at 14.4 VA 48 V at 70 °C (load factor 0.4) AC-15: 300000 cycles at 48 VA 48 V at -25...60 °C (load factor 0.4) AC-15: 300000 cycles at 28.8 VA 48 V at 70 °C (load factor 0.4) AC-15: 100000 cycles at 96 VA 48 V at -25...60 °C (load factor 0.4) AC-15: 100000 cycles at 57.6 VA 48 V at 70 °C (load factor 0.4) AC-15: 1000000 cycles at 10 VA 100...120 V at -25...60 °C (load factor 0.4) AC-15: 1000000 cycles at 6 VA 100...120 V at 70 °C (load factor 0.4) AC-15: 300000 cycles at 50 VA 100...120 V at -25...60 °C (load factor 0.4) AC-15: 300000 cycles at 30 VA 100...120 V at 70 °C (load factor 0.4) AC-15: 200000 cycles at 110 VA 100...120 V at -25...60 °C (load factor 0.4) AC-15: 200000 cycles at 66 VA 100...120 V at 70 °C (load factor 0.4) AC-15: 70000 cycles at 220 VA 100...120 V at -25...60 °C (load factor 0.4) AC-15: 70000 cycles at 132 VA 100...120 V at 70 °C (load factor 0.4) AC-15: 1000000 cycles at 10 VA 200...250 V at -25...60 °C (load factor 0.4) AC-15: 1000000 cycles at 6 VA 200...250 V at 70 °C (load factor 0.4) AC-15: 500000 cycles at 50 VA 200...250 V at -25...60 °C (load factor 0.4) AC-15: 500000 cycles at 30 VA 200...250 V at 70 °C (load factor 0.4) AC-15: 200000 cycles at 110 VA 200...250 V at -25...60 °C (load factor 0.4) AC-15: 200000 cycles at 66 VA 200...250 V at 70 °C (load factor 0.4) AC-15: 150000 cycles at 220 VA 200...250 V at -25...60 °C (load factor 0.4) AC-15: 150000 cycles at 132 VA 200...250 V at 70 °C (load factor 0.4) DC-12: 200000 cycles at 24 W 24 V at -25...60 °C DC-12: 200000 cycles at 14.4 W 24 V at 70 °C DC-12: 150000 cycles at 48 W 24 V at -25...60 °C DC-12: 150000 cycles at 28.8 W 24 V at 70 °C DC-12: 150000 cycles at 40 W 48...60 V at -25...60 °C DC-12: 150000 cycles at 24 W 48...60 V at 70 °C DC-12: 100000 cycles at 45 W 100...125 V at -25...60 °C DC-12: 60000 cycles at 45 W 100...125 V at 70 °C DC-13: 100000 cycles at 10 W 24 V at -25...60 °C DC-13: 100000 cycles at 6 W 24 V at 70 °C DC-13: 60000 cycles at 24 W 24 V at -25...60 °C DC-13: 60000 cycles at 14.4 W 24 V at 70 °C DC-13: 40000 cycles at 48 W 24 V at -25...60 °C DC-13: 40000 cycles at 28.8 W 24 V at 70 °C DC-13: 40000 cycles at 40 W 48...60 V at -25...60 °C DC-13: 40000 cycles at 24 W 48...60 V at 70 °C DC-13: 100000 cycles at 15 W 100...125 V at -25...60 °C DC-13: 40000 cycles at 15 W 100...125 V at 70 °C 1 LED (green) RUN 1 LED per channel (green) channel diagnostic 1 LED (red) ERR 1 LED (red) I/O

Net weight

Status LED

0.169 kg

Environment

IP degree of protection

IP20

Environmental characteristic	Gas resistant class Gx	
	Gas resistant class 3C4	
	Dust resistant class 3S4	
	Sand resistant class 3S4	
	Salt resistant level 2	
	Mold growth resistant class 3B2	
	Fundal shore resistant class 3B2	
	rungar spore resistant class 302	
Dielectric strength	1780 V AC at 50/60 Hz 1 min	
Vibration resistance	3 gn	
Shock resistance	30 gn	
Ambient air temperature for storage	-4085 °C	
Ambient air temperature for operation	-2570 °C	
Relative humidity	095 % at 60 °C without condensation	
Protective treatment	Conformal coating	
Operating altitude	02000 m	
	20005000 m with derating factor	

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	5.500 cm
Package 1 Width	11.600 cm
Package 1 Length	12.300 cm
Package 1 Weight	207.000 g
Unit Type of Package 2	S02
Number of Units in Package 2	15
Package 2 Height	15.000 cm
Package 2 Width	30.000 cm
Package 2 Length	40.000 cm
Package 2 Weight	3.442 kg

Life Is On Scheider

Lenvironmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing "Use Better, Use Longer, Use Again" campaign to extend product lifetimes and recyclability.

Environmental Data explained >

How we assess product sustainability >

Environmental footprint Carbon footprint (kg.eq.CO2 per CR, Total Life cycle) 158

Environmental Disclosure

Product Environmental Profile

Use Better

$^{\mbox{\footnotesize \sc only}}$ Materials and Substances	
Packaging made with recycled cardboard	Yes
Packaging without single use plastic	Yes
EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope)
REACh Regulation	REACh Declaration

Use Again

$^{\circlearrowright}$ Repack and remanufacture			
Circularity Profile	End of Life Information		
Take-back	No		
WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins		

Dimensions Drawings

Modules Mounted on Racks

Dimensions



(1) With removable terminal block (cage, screw or spring).

(2) With FCN connector.

(3) On AM1 ED rail: 35 mm wide, 15 mm deep. Only possible with BMXXBP0400/0400H/0600/0600H/0800/0800H rack.

Rack references	a in mm	a in in.
BMXXBP0400 and BMXXBP0400H	242.4	09.54
BMXXBP0600 and BMXXBP0600H	307.6	12.11
BMXXBP0800 and BMXXBP0800H	372.8	14.68
BMXXBP1200 and BMXXBP1200H	503.2	19.81

Product datasheet

Connections and Schema

Connecting the Module

Output Circuit Diagram



- (1) Module
- (2) Output
- (3) Command
- (4) Pre-actuator
- (5) Power supply

Module Connection



(1) Pre-actuator

(2) Power supply : 24...125 Vdc or 24...240 Vac

Product datasheet

BMXDRA0815H

(3) Fuse : Use appropriate fast-blow fuse for each relay

(4) We recommend installing this type of protection on the terminals of each pre-actuator $N\!/C$: Not connected