

Motor circuit breaker, TeSys GV4, 3P, 12.5A, Icu 50kA, magnetic, lugs terminals

GV4L12N6

Main

Range of product	TeSys GV4
Range	TeSys Deca
Device short name	GV4L
product name	TeSys GV4
Product or component type	Motor circuit breaker
Device application	Motor protection
Trip unit technology	Magnetic Electronic

Complementary

o o mpromontary					
Poles description	3P				
Utilisation category	Category A conforming to IEC 60947-2				
	AC-3 conforming to IEC 60947-4-1				
Operating position	Any position				
Motor power kW	3 kW at 400415 V AC 50/60 Hz				
	3 kW at 500 V AC 50/60 Hz				
	4 kW at 500 V AC 50/60 Hz				
	5.5 kW at 660690 V AC 50/60 Hz				
	7.5 kW at 660690 V AC 50/60 Hz				
	4 kW at 400415 V AC 50/60 Hz				
	5.5 kW at 400415 V AC 50/60 Hz				
	5.5 kW at 500 V AC 50/60 Hz				
	7.5 kW at 500 V AC 50/60 Hz				
	9 kW at 660690 V AC 50/60 Hz				
	11 kW at 660690 V AC 50/60 Hz				
Breaking capacity	100 kA Icu at 220240 V AC 50/60 Hz conforming to IEC 60947-2				
	50 kA Icu at 380415 V AC 50/60 Hz conforming to IEC 60947-2				
	50 kA Icu at 440 V AC 50/60 Hz conforming to IEC 60947-2				
	15 kA Icu at 525 V AC 50/60 Hz conforming to IEC 60947-2				
	8 kA Icu at 660690 V AC 50/60 Hz conforming to IEC 60947-2				
	25 kA Icu at 500 V AC 50/60 Hz conforming to IEC 60947-2				
Control type	Rotary handle				
[In] rated current	12.5 A				
Magnetic tripping current	75175 A				
[Ue] rated operational voltage	690 V AC 50/60 Hz conforming to IEC 60947-2				
[Ui] rated insulation voltage	800 V AC 50/60 Hz conforming to IEC 60947-2				
[Ith] conventional free air thermal current	115 A conforming to IEC 60947-4-1				
[Uimp] rated impulse withstand voltage	8 kV conforming to IEC 60947-2				
Power dissipation per pole	6.1 W				

Mechanical durability	40000 cycles					
Electrical durability	40000 cycles for AC-3 at 440 V In/2 40000 cycles for AC-3 at 440 V In					
Maximum operating rate	25 cyc/h					
Rated duty	Continuous conforming to IEC 60947-4-1					
Connection pitch	27 mm without spreaders 35 mm with spreaders					
Connections - terminals	Lugs-ring terminals					
Tightening torque	9 N.m for cable 1695 mm ² 5 N.m for cable 1.510 mm ²					
Mechanical robustness	Vibrations: +/- 1 mm 213.2 Hz conforming to IEC 60068-2-6 Vibrations: 0.7 gn 13.2100 Hz conforming to IEC 60068-2-6 Shocks: 15 gn 11 ms conforming to IEC 60068-2-27					
Height	155 mm					
Width	81 mm					
Depth	165 mm					
Net weight	1.65 kg					
Colour	Grey (RAL 7016)					
Suitability for isolation	Yes conforming to IEC 60947-1					

Environment

Standards	EN/IEC 60947-4-1 EN/IEC 60947-2
Product certifications	IEC CCC EAC EU-RO MR
Climatic withstand	conforming to IACS E10
IK degree of protection	IK07 conforming to IEC 62262
pollution degree	3
IP degree of protection	IP40 conforming to IEC 60529
Ambient air temperature for storage	-5085 °C
Fire resistance	960 °C conforming to IEC 60695-2-11
Operating altitude	5000 m
Ambient air temperature for operation	-2570 °C

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	21 cm
Package 1 Width	10.5 cm
Package 1 Length	22 cm
Package 1 Weight	1.634 kg

Contractual warranty

Warranty 18 months



Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing "Use Better, Use Longer, Use Again" campaign to extend product lifetimes and recyclability.

Environmental Data explained >

How we assess product sustainability >

☑ Environmental footprint

Environmental Disclosure

Product Environmental Profile

Use Better


Recycled metal content at CR level	0
Packaging made with recycled cardboard	Yes
Packaging without single use plastic	No
EU RoHS Directive	Compliant
SCIP Number	1b259a2c-3a3c-401a-acdd-f0837efd4018
REACh Regulation	REACh Declaration
Halogen content performance	Halogen free plastic parts product
PVC free	Yes

Use Again

○ Repack and remanufacture	
Circularity Profile	End of Life Information
Take-back	No
WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins

Performance Curves

Tripping Curves for GV4L and GV4LE Combined with Thermal Overload Relay LRD or LR9 Average Operating Times at 20 °C Related to Multiples of the Setting Current GV4L02 and GV4LE02 to 12 with LRD05 to LRD14, GV4L80 and GV4LE80 with LRD3363




- 1 3 poles from cold state
- 2 2 poles from cold state
- 3 3 poles from hot state
- 4 6...14 lr
- A Thermal overload relay protection zone
- B GV4L protection zone

GV4L25 and GV4LE25 with LRD 318, LRD325 GV4L50 AND GV4LE50 with LRD 332, LRD 340, LRD 350


Product datasheet

GV4L12N6



- 1 3 poles from cold state
- 2 2 poles from cold state
- 3 3 poles from hot state
- 4 6...14 lr
- A Thermal overload relay protection zone
- B GV4L protection zone

GV4L115 and GV4LE115 with Class 10 LR9F5367, LR9D5369 and Class 20 LR9D5567, LR9F5569




- 1 Cold state curve
- 2 Hot state curve
- 3 6...14 lr

Current Limitation on Short-Circuit for GV4L, GV4LE (3-Phase 400/415 V)

Dynamic Stress

I peak = f (prospective lsc) at 1.05 Ue = 435 V




- 1 Maximum peak current
- 2 GV4L115
- 3 GV4L80
- 4 GV4L50
- 5 GV4L25
- 6 GV4L12
- 7 GV4L07
- 8 GV4L03
- 9 GV4L02

Current Limitation on Short-Circuit for GV4L, GV4LE + Thermal Overload Relay LRD or LR9 (3-Phase 400/415 V)

Dynamic Stress

I peak = f (prospective lsc) at 1.05 Ue = 435 V




- 1 Maximum peak current
- 2 GV4L115 + LR9D5367 or LR9F5367
- 3 GV4L80 + LRD3361
- 4 GV4L50 + LRD340
- 5 GV4L25 + LRD325
- 6 GV4L12 + LRD313
- 7 GV4L07 + LRD12
- 8 GV4L03 + LRD07
- 9 GV4L02 + LRD07

Thermal Limit on Short-Circuit for GV4L, GV4LE

Thermal Limit in A²s

Sum of I^2 dt = f (prospective Isc) at 1.05 Ue = 435 V

GV4L12N6




- 1 GV4L115
- 2 GV4L80
- 3 GV4L50
- 4 GV4L25
- 5 GV4L12
- 6 GV4L07
- 7 GV4L03
- 8 GV4L02

Current Limitation on Short-Circuit for GV4L, GV4LE + Thermal Overload Relay LRD or LR9

Thermal Limit in kA in the Magnetic Operating Zone

Sum of I^2 dt = f (prospective Isc) at 1.05 Ue = 435 V




- 1 GV4L115 + LR9D5367 or LR9F5367
- 2 GV4L80 + LRD3361
- 3 GV4L50 + LRD340
- 4 GV4L25 + LRD325
- 5 GV4L12 + LRD313
- 6 GV4L07+ LRD12
- 7 GV4L03+ LRD07
- 8 GV4L02 + LRD07


Dimensions Drawings

GV4 with Toggle: GV4LE, GV4PE, GV4PEM

With EverLink[®] Connector




With Crimp Lug Connector



- (1) Interphases barriers
- (2) Long terminal shield


GV4 with Rotary Handle: GV4L, GV4P, or GV4LE, GV4PE, GV4PEM with GV4ADN01, GV4ADN02 Direct Mounting Rotary Handle

Dimensions




GV4L, GV4P, GV4LE, GV4PE, GV4PEM


Panel Mounting with M4 Screws



Door Cut-Out for Rotary Handle



Minimum Safety Clearance



Toggle-type, rotary handle-type: identical clearance values.

roggie-type, rotary riari	ule-type, luell	licai	Cicai	arice vail	JC3.	
Safety Clearance (mm)						
	Painted Sheet Metal			Bare Sheet Metal		
	Α	В	С	Α	В	С
No accessory	30	0	0	40	0	5
Interphase barriers	0	0	0	0	0	5
Long terminal shield	0	0	0	0	0	5

Connections and Schema

Magnetic Motor Circuit Breakers

GV4L, GV4LE

