

single function relay, Harmony Timer Relays, 8A, 2CO, 0.05s... 300h, symmetrical flashing, 24...240V AC DC

RE22R2DMR

Main

Range of product	Harmony Timer Relays
Discrete output type	Relay
Product or component type	Modular timing relay
Device short name	RE22
Nominal output current	8 A

Complementary

Contacts type and composition	C/O timed contact, cadmium free C/O timed or instantaneous contact, cadmium free	
Time delay type	Symmetrical flashing	
Time delay range	110 s 30300 min	
	330 s	
	10100 s	
	30300 h	
	30300 s	
	330 min	
	0.33 s	
	0.051 s	
	330 h	
Control type	Rotary knob	
	Diagnostic button	
	Potentiometer external	
[Us] rated supply voltage	24240 V AC/DC 50/60 Hz	
Release input voltage	<= 2.4 V	
Voltage range	0.851.1 Us	
Supply frequency	5060 Hz +/- 5 %	
Connections - terminals	Screw terminals, 1 x 0.51 x 3.3 mm² (AWG 20AWG 12) solid without cable end Screw terminals, 2 x 0.52 x 2.5 mm² (AWG 20AWG 14) solid without cable end Screw terminals, 1 x 0.21 x 2.5 mm² (AWG 24AWG 14) flexible with cable end Screw terminals, 2 x 0.22 x 1.5 mm² (AWG 24AWG 16) flexible with cable end	
Tightening torque	0.61 N.m conforming to IEC 60947-1	
Housing material	Self-extinguishing	
Repeat accuracy	+/- 0.5 % conforming to IEC 61812-1	
Temperature drift	+/- 0.05 %/°C	
Voltage drift	+/- 0.2 %/V	
Setting accuracy of time delay	+/- 10 % of full scale at 25 °C conforming to IEC 61812-1	
Time delay type	Symmetrical flashing - D- Symmetrical flashing relay (starting pulse-off) Symmetrical flashing - Dw- Symmetrical flashing relay (starting pulse-off) w/ retrigger/ restart	

Control signal pulse width	100 ms with load in parallel 30 ms	
Insulation resistance	100 MOhm at 500 V DC conforming to IEC 60664-1	
Recovery time	120 ms on de-energisation	
Immunity to microbreaks	10 ms	
Power consumption in VA	3 VA at 240 V AC	
Power consumption in W	1.5 W at 240 V DC	
Switching capacity in VA	2000 VA	
Minimum switching current	10 mA at 5 V DC	
Maximum switching current	8 A	
Maximum switching voltage	250 V AC	
Electrical durability	100000 cycles, 8 A at 250 V, AC-1 100000 cycles, 2 A at 24 V, DC-1	
Mechanical durability	10000000 cycles	
Rated impulse withstand voltage	5 kV for 1.250 μs conforming to IEC 60664-1	
Power on delay	100 ms	
Creepage distance	4 kV/3 conforming to IEC 60664-1	
Overvoltage category	III conforming to IEC 60664-1	
Safety reliability data	B10d = 200000 MTTFd = 216.8 years	
Mounting position	Any position	
Mounting support	35 mm DIN rail conforming to IEC 60715	
Status LED	LED backlight green (steady) for dial pointer indication LED yellow (steady) for output relay energised LED yellow (fast flashing) for timing in progress and output relay de-energised LED yellow (slow flashing) for timing in progress and output relay energised	
Function available	D- Symmetrical flashing relay (starting pulse-off)-2 C/O Dw- Symmetrical flashing relay (starting pulse-off) w/ retrigger/restart-2 C/O	
Width	22.5 mm	
Net weight	0.105 kg	
Control type	With test button	
Number of functions	2	

Environment

Dielectric strength	2.5 kV for 1 mA/1 minute at 50 Hz between relay output and power supply with basic insulation conforming to IEC 61812-1
Standards	IEC 61812-1 UL 508
Directives	2004/108/EC - electromagnetic compatibility 2006/95/EC - low voltage directive
Product certifications	CCC
	CSA
	RCM
	GL
	CE
	UL
	EAC
Ambient air temperature for operation	-2060 °C

Ambient air temperature for storage	-4070 °C
IP degree of protection	IP40 housing: conforming to IEC 60529 IP20 terminals: conforming to IEC 60529 IP50 front panel: conforming to IEC 60529
Pollution degree	3 conforming to IEC 60664-1
Vibration resistance	20 m/s² (f= 10150 Hz) conforming to IEC 60068-2-6
Shock resistance	15 gn not operating for 11 ms conforming to IEC 60068-2-27 5 gn in operation for 11 ms conforming to IEC 60068-2-27
Relative humidity	95 % at 2555 °C
Electromagnetic compatibility	Fast transients immunity test - test level: 1 kV level 3 (capacitive connecting clip) conforming to IEC 61000-4-4 Surge immunity test - test level: 1 kV level 3 (differential mode) conforming to IEC 61000-4-5 Surge immunity test - test level: 2 kV level 3 (common mode) conforming to IEC 61000-4-5 Electrostatic discharge - test level: 6 kV level 3 (contact discharge) conforming to IEC 61000-4-2 Electrostatic discharge - test level: 8 kV level 3 (air discharge) conforming to IEC 61000-4-2 Radiated radio-frequency electromagnetic field immunity test - test level: 10 V/m level 3 (80 MHz1 GHz) conforming to IEC 61000-4-3 Conducted RF disturbances - test level: 10 V level 3 (0.1580 MHz) conforming to IEC 61000-4-6 Fast transient bursts - test level: 2 kV level 3 (direct contact) conforming to IEC 61000-4-4 Immunity to microbreaks and voltage drops - test level: 30 % (500 ms) conforming to IEC 61000-4-11 Immunity to microbreaks and voltage drops - test level: 100 % (20 ms) conforming to IEC 61000-4-11

Packing Units

r adming dimes	
Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	2.600 cm
Package 1 Width	8.200 cm
Package 1 Length	9.500 cm
Package 1 Weight	114.000 g
Unit Type of Package 2	S02
Number of Units in Package 2	40
Package 2 Height	15.000 cm
Package 2 Width	30.000 cm
Package 2 Length	40.000 cm
Package 2 Weight	5.080 kg



Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing "Use Better, Use Longer, Use Again" campaign to extend product lifetimes and recyclability.

Environmental Data explained >

How we assess product sustainability >

⊘ Environmental footprint		
Carbon footprint (kg.eq.CO2 per CR, Total Life cycle)	43	

Use Better


⊗ Materials and Substances	
Packaging made with recycled cardboard	Yes
Packaging without single use plastic	Yes
EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope)
SCIP Number	7bdc2711-0ad2-427c-8ece-532c5e9f09d7
REACh Regulation	REACh Declaration

Use Again

☼ Repack and remanufacture		
Take-back	No	

Dimensions Drawings

Dimensions




Product datasheet

RE22R2DMR

Connections and Schema

Wiring Diagram




Technical Description

Function D: Symmetrical Flashing Relay (Starting Pulse Off)


Description

On energisation of power supply, output(s) R starts at its/their initial state for timing duration T then change(s) to output(s) R close(s) for the same timing duration T.This cycle is repeated indefintely until power supply removal.Specially for RE17*, RE22R2AMU, RE22R2MMW, RE22R2MMU, RE22R2MJU,this D function can only be initiated by energizing Y1 permanently.The second output (R2) can be either timed (when set to "TIMED") or instantaneous (when set to "INST").


Function: 1 Output




Function: 2 Outputs



Function: 1 Output with Retrigger / Restart Control



Function: 2 Output with Retrigger / Restart Control




RE22R2DMR

Function DW: Symmetrical Flashing Relay (Starting Pulse Off) & With Retrigger / Restart Control


Description

On energisation of power supply, output(s) R starts at its/their initial state for timing duration T then change(s) to output(s) R close(s) for the same timing duration T.This cycle is repeated indefintely until power supply removal.Specially for RE17*, RE22R2AMU, RE22R2MMW, RE22R2MMU, RE22R2MJU,this D function can only be initiated by energizing Y1 permanently.The second output (R2) can be either timed (when set to "TIMED") or instantaneous (when set to "INST").

Function: 1 Output



Function: 2 Outputs



Legend



	that cloud
U -	Supply
T -	Timing period
R1/R2 -	2 timed outputs
R2 inst	The second output is instantaneous if the right position is selected
Y1 -	Retrigger / Restart control

Technical Illustration

Dimensions

