Catalogue No: WPFLRF210LEDPRMT

PLATINUM F/LIGHT LED W/P RF 2 x 10W NON-MAINT W/REM LAMP HD

Stanilite Emergency and Exit Lighting > Platinum > Monitored Platinum > Platinum Flood RF





Platinum Flood Light LED Weather Proof Nexus RF 2x10W Non-Maintained with Remote Lamp Head

- Compliance to latest ASNZS2293.3:2018.
- Reliable Stanilite Brand.
- LED energy efficient products.
- 10 year product design life.
- Lithium ion phosphate batteries.
- Advanced power management.

Representative Photo Only (actual product may vary based on configuration selections)

SPECIFICATIONS	
Component Type Emergency Lighting	Flood
Testing System	Nexus RF Infinity
Operating Mode	Non-Maintained
Operating Voltage	240 VAC
Rated Frequency	50 Hz
Power Consumption	1.5 W
Mounting	Surface - Universal
LED Life	100,000 hours
Battery Type	LiFePO4
Height	190 mm
Width	130 mm
Depth	380 mm
Base Colour	Grey
Battery Replacement	0301316PB
IP Rating	IP65
Standards Compliance	ASNZS CISPR 15 ASNZS2293.3:2018 ASNZS60598.1:2017 ASNZS60598.2.22:2005



Catalogue No: WPFLRF210LEDPRMT

PLATINUM F/LIGHT LED W/P RF 2 x 10W NON-MAINT W/REM LAMP HD

Stanilite Emergency and Exit Lighting > Platinum > Monitored Platinum > Platinum Flood RF



REFERENCES	
IECEx Certificate	
Supplier Declaration of Conformity:	Flood Light Weatherproof Emergency Luminaire, LifePO4 Battery_Supplier Declaration of Conformity (SDoC)
Installation Guide:	Flood Light LED WeatherproofStandard, Nexus LX, Nexus RF_Installation Instructions
User Manual:	-
Manufacturer Datasheet:	Platinum Flood Light LED Weatherproof NexusManufacturer Datasheet
Manufacturer Catalogue & Product Selection:	-

