Catalogue No: **PWEXNXSLEDP3** PLATINUM EXIT LED WEATHER PROOF NEXUS LX PICTO R

Stanilite Emergency and Exit Lighting > Platinum > Monitored Platinum > Platinum Exit LX



Platinum Exit LED Weather Proof Nexus LX Picto R

- Compliance to latest ASNZS2293.3:2018. •
- Reliable Stanilite Brand.
- LED energy efficient products. •
- 10 year product design life. •
- Lithium ion phosphate batteries. •
- Advanced power management.



Representative Photo Only (actual product may vary based on configuration selections)

SPECIFICATIONS	
Component Type Emergency Lighting	Exit
Testing System	Nexus LX
Operating Mode	Maintained
Operating Voltage	240 VAC
Rated Frequency	50 Hz
Power Consumption	3.2 W
Mounting	Surface - Wall
Viewing Distance	24 meters
LED Life	100,000 hours
Photometric Classification	C0:D1.25 C90:C1.25
Battery Type	LiFePO4
Height	190 mm
Width	130 mm
Depth	380 mm
Base Colour	Grey
Diffuser Colour	White on Green
Battery Replacement	0301301P
IP Rating	IP65
Standards Compliance	ASNZS CISPR 15 ASNZS2293.3:2018 ASNZS60598.1:2017 ASNZS60598.2.22:2005

Catalogue No: **PWEXNXSLEDP3**

PLATINUM EXIT LED WEATHER PROOF NEXUS LX PICTO R

Stanilite Emergency and Exit Lighting > Platinum > Monitored Platinum > Platinum Exit LX

REFERENCES	
IECEx Certificate	=
Supplier Declaration of Conformity:	Weatherproof LED Exit Sign, NiCad or LifePO4 Battery_Supplier Declaration of Conformity (SDoC)
Installation Guide:	Stanilite Exit LED Weatherproof Standard, Nexus LX, Nexus RF_Installation Instructions
User Manual:	-
Manufacturer Datasheet:	Platinum Exit LED Weatherproof NexusManufacturer Datasheet
Manufacturer Catalogue & Product Selection:	-



NHP