



Platinum Range Surface Mount Spitfire 2 LED RF Black

- Compliance to latest ASNZS2293.3:2018.
- Reliable Stanilite Brand.
- LED energy efficient products.
- 10 year product design life.
- Lithium ion phosphate batteries.
- Advanced power management.

Representative Photo Only
(actual product may vary based on configuration selections)

SPECIFICATIONS	
Component Type	Emergency Lighting Spitfire
Testing System	Nexus RF Infinity
Operating Mode	Non-Maintained
Operating Voltage	240 VAC
Rated Frequency	50 Hz
Power Consumption	1.0 W
Mounting	Surface - Ceiling
LED Life	100,000 hours
Photometric Classification	C0:D63 C90:D63
Battery Type	LiFePO4
Height	68 mm
Width	167 mm
Depth	288 mm
Base Colour	Black
Battery Replacement	0301303P
IP Rating	IP20
Standards Compliance	ASNZS CISPR 15 ASNZS2293.3:2018 ASNZS60598.1:2017 ASNZS60598.2.22:2005

Catalogue No: **SFBNRF2LEDPBLK**

PLATINUM RANGE SURFACE MOUNT SPITFIRE 2 LED RF BLACK

Stanilite Emergency and Exit Lighting > Platinum > Monitored Platinum > Platinum Spitfire RF



REFERENCES

IECEX Certificate -

Supplier Declaration of
Conformity: -

Installation Guide: -

User Manual: -

Manufacturer Datasheet: [Platinum Spitfire LED Surface Mount Theatre Mask Nexus Non-maintained_Manufacturer Datasheet](#)

Manufacturer Catalogue
& Product Selection: -