

Platinum Exit LED Edgelit Recessed Nexus LX Pictograph (Original Style Square Diffuser)

- Compliance to latest ASNZS2293.3:2018.
- Reliable Stanilite Brand.
- LED energy efficient products.
- 10 year product design life.
- Lithium ion phosphate batteries.
- Advanced power management.



Representative Photo Only
(actual product may vary based on configuration selections)

SPECIFICATIONS

Component Type	Emergency Lighting	Exit
Testing System		Nexus LX
Operating Mode		Maintained
Operating Voltage		240 VAC
Rated Frequency		50 Hz
Power Consumption		2.4 W
Mounting		Recessed
Viewing Distance		24 meters
LED Life		100,000 hours
Photometric Classification		C0:D2 C90:E1.6
Battery Type		LiFePO4
Height		251 mm
Width		121 mm
Depth		422 mm
Base Colour		White
Diffuser Colour		White on Green
Battery Replacement		0301304P
IP Rating		IP20
Standards Compliance		ASNZS CISPR 15 ASNZS2293.3:2018 ASNZS60598.1:2017 ASNZS60598.2.22:2005

Catalogue No: **PLRONXSLEDP**
PLATINUM EXIT LED E/LIT REC LX PICTO (ORIG STYLE SQ DIFF)

Stanilite Emergency and Exit Lighting > Platinum > Monitored Platinum > Platinum Exit LX



REFERENCES

IECEX Certificate	-
Supplier Declaration of Conformity:	Legend Recessed PLRO LED Exit Sign, NiMH or LifePO4 Battery_Supplier Declaration of Conformity (SDoC)
Installation Guide:	Stanilite Exit LED Edgelit Recessed Emergency, Nexus LX, Nexus RF_Installation Instructions
User Manual:	-
Manufacturer Datasheet:	Platinum Exit LED Edgelit Recessed Nexus, Original Style Square Diffuser_Manufacturer Datasheet
Manufacturer Catalogue & Product Selection:	-