



Platinum Power Supply Module to Suit Platinum IP65 Surface Mount 2 LED Spitfire RF

- Compliance to latest ASNZS2293.3:2018.
- Reliable Stanilite Brand.
- LED energy efficient products.
- 10 year product design life.
- Lithium ion phosphate batteries.
- Advanced power management.

Representative Photo Only
(actual product may vary based on configuration selections)

SPECIFICATIONS

Component Type Emergency Lighting	Spitfire
Testing System	Nexus RF Infinity
Operating Mode	Non-Maintained
Operating Voltage	240 VAC
Rated Frequency	50 Hz
Power Consumption	1.0 W
Mounting	Surface - Ceiling
Photometric Classification	C0:D63 C90:D63
Battery Type	LiFePO4
Height	130 mm
Width	188 mm
Depth	278 mm
Base Colour	Grey
Battery Replacement	0301303P
IP Rating	IP67
Standards Compliance	ASNZS CISPR 15 ASNZS2293.3:2018 ASNZS60598.1:2017 ASNZS60598.2.22:2005

Catalogue No: **SFBWPNRF2LEDPPSU**

PLATINUM P/S MOD PLATINUM IP65 S/MNT 2 LED SPITFIRE RF

Stanilite Emergency and Exit Lighting > Platinum > Monitored Platinum > Platinum Spitfire RF



REFERENCES

IECEX Certificate	-
Supplier Declaration of Conformity:	Spitfire Weatherproof Emergency, NiCad or LifePO4 Battery_Supplier Declaration of Conformity (SDoC)
Installation Guide:	-
User Manual:	-
Manufacturer Datasheet:	-
Manufacturer Catalogue & Product Selection:	-