



Platinum Spitfire Dual LED Surface Mount Nexus LX

- Compliance to latest ASNZS2293.3:2018.
- Reliable Stanilite Brand.
- LED energy efficient products.
- 10 year product design life.
- Lithium ion phosphate batteries.
- Advanced power management.



Representative Photo Only
(actual product may vary based on configuration selections)

| SPECIFICATIONS | |
|----------------------------|----------------------|
| Component Type | Emergency Lighting |
| Testing System | Spitfire |
| Operating Mode | Nexus LX |
| Operating Voltage | Non-Maintained |
| Rated Frequency | 240 VAC |
| Power Consumption | 50 Hz |
| Mounting | 1.0 W |
| LED Life | Surface - Ceiling |
| Photometric Classification | 100,000 hours |
| Battery Type | C0:D63 C90:D63 |
| Height | LiFePO4 |
| Width | 68 mm |
| Depth | 167 mm |
| Base Colour | 288 mm |
| Battery Replacement | White |
| IP Rating | 0301303P |
| Standards Compliance | IP20 |
| | ASNZS CISPR 15 |
| | ASNZS2293.3:2018 |
| | ASNZS60598.1:2017 |
| | ASNZS60598.2.22:2005 |



REFERENCES

IECEX Certificate -

Supplier Declaration of
Conformity: -

Installation Guide: [Spitfire LED surface MountStandard, Nexus LX, Nexus RF_ Installation Instructions](#)

User Manual: -

Manufacturer Datasheet: [Platinum Spitfire LED Surface Mount Nexus Non-maintained_ Manufacturer Datasheet](#)

Manufacturer Catalogue
& Product Selection: -