## Catalogue No: **SFNXS2LEDP**

#### PLATINUM SPITFIRE DUAL LED RECESSED NEXUS LX

Stanilite Emergency and Exit Lighting > Platinum > Monitored Platinum > Plati





#### Platinum Spitfire Dual LED Recessed Nexus LX

- Compliance to latest ASNZS2293.3:2018.
- Reliable Stanilite Brand.
- LED energy efficient products.
- 10 year product design life.
- Lithium ion phosphate batteries.
- Advanced power management.

Representative Photo Only (actual product may vary based on configuration selections)

SPECIFICATIONS	
Component Type Emergency Lighting	Spitfire
Testing System	Nexus LX
Operating Mode	Non-Maintained
Operating Voltage	240 VAC
Rated Frequency	50 Hz
Power Consumption	1.0 W
Mounting	Recessed
LED Life	100,000 hours
Photometric Classification	C0:D63 C90:D63
Battery Type	LiFePO4
Base Colour	White
Battery Replacement	0301303P
IP Rating	IP20
Standards Compliance	ASNZS CISPR 15 ASNZS2293.3:2018 ASNZS60598.1:2017 ASNZS60598.2.22:2005



# Catalogue No: **SFNXS2LEDP**

### PLATINUM SPITFIRE DUAL LED RECESSED NEXUS LX

Stanilite Emergency and Exit Lighting > Platinum > Monitored Platinum > Platinum Spitfire LX



REFERENCES	
IECEx Certificate	-
Supplier Declaration of Conformity:	Spitfire Recessed Emergency, NiCad or LifePO4 Battery_Supplier Declaration of Conformity (SDoC)
Installation Guide:	-
User Manual:	-
Manufacturer Datasheet:	Platinum Spitfire LED Recessed DALI Non-Maintained Manufacturer Datasheet
Manufacturer Catalogue & Product Selection:	-

