

Platinum Range Surface Mount Weather Proof 1 LED



- Compliance to latest ASNZS2293.3:2018.
- Reliable Stanilite Brand.
- LED energy efficient products.
- 10 year product design life.
- Lithium ion phosphate batteries.
- Advanced power management.

Representative Photo Only
(actual product may vary based on configuration selections)

SPECIFICATIONS

| | | |
|----------------------------|--------------------|---|
| Component Type | Emergency Lighting | Spitfire |
| Testing System | | Single Point Unit |
| Operating Mode | | Non-Maintained |
| Operating Voltage | | 240 VAC |
| Rated Frequency | | 50 Hz |
| Power Consumption | | 1.0 W |
| Mounting | | Surface - Ceiling |
| LED Life | | 100,000 hours |
| Photometric Classification | | C0:D40 C90:D40 |
| Battery Type | | LiFePO4 |
| Height | | 130 mm |
| Width | | 188 mm |
| Depth | | 278 mm |
| Base Colour | | Grey |
| Battery Replacement | | 0301301P |
| IP Rating | | IP67 |
| Standards Compliance | | ASNZS CISPR 15 ASNZS2293.3:2018 ASNZS60598.1:2017 ASNZS60598.2.22:2005 |

Catalogue No: **SFBWP1LEDP**

PLATINUM RANGE SURFACE MOUNT WEATHER PROOF 1 LED

Stanilite Emergency and Exit Lighting > Platinum > Single Point Platinum > Platinum Spitfire EM



REFERENCES

IECEX Certificate

-

Supplier Declaration of
Conformity:

[Spitfire Weatherproof Emergency, NiCad or LifePO4 Battery_Supplier Declaration of Conformity \(SDoC\)](#)

Installation Guide:

-

User Manual:

-

Manufacturer Datasheet:

[Platinum Spitfire LED Weatherproof Non-maintained_Manufacturer Datasheet](#)

Manufacturer Catalogue
& Product Selection:

-