

Platinum Exit LED Weather Proof Remote Picto - Body Only



- Compliance to latest ASNZS2293.3:2018.
- Reliable Stanilite Brand.
- LED energy efficient products.
- 10 year product design life.
- Lithium ion phosphate batteries.
- Advanced power management.

Representative Photo Only
(actual product may vary based on configuration selections)

SPECIFICATIONS

Component Type	Emergency Lighting	Exit
Testing System		Single Point Unit
Operating Mode		Maintained
Operating Voltage		240 VAC
Rated Frequency		50 Hz
Mounting		Surface - Wall
Viewing Distance		24 meters
LED Life		100,000 hours
Photometric Classification		C0:D1.25 C90:C1.25
Battery Type		LiFePO4
Height		190 mm
Width		130 mm
Depth		380 mm
Base Colour		Grey
Diffuser Colour		White on Green
IP Rating		IP65
Standards Compliance		ASNZS CISPR 15 ASNZS2293.3:2018 ASNZS60598.1:2017 ASNZS60598.2.22:2005



REFERENCES	
IECEX Certificate	-
Supplier Declaration of Conformity:	-
Installation Guide:	Stanilite Exit LED Weatherproof Standard, Nexus LX, Nexus RF_Installation Instructions
User Manual:	-
Manufacturer Datasheet:	Platinum Exit LED Weatherproof Remote_Manufacturer Datasheet
Manufacturer Catalogue & Product Selection:	-