

Catalogue No: **SFB1LEDBLK**  
**SPITFIRE 1 LED SURFACE MOUNT BLACK**

Stanilite Emergency and Exit Lighting > Signature > Single Point Signature > Signature Spitfire EM



Spitfire 1 LED Surface Mount Black

- Compliance to latest ASNZS2293.3:2018.
- Reliable Stanilite Brand.
- Hi-temp NiCad batteries.

Representative Photo Only  
(actual product may vary based on configuration selections)

**SPECIFICATIONS**

Component Type	Emergency Lighting	Spitfire
Testing System		Single Point Unit
Operating Mode		Non-Maintained
Operating Voltage		240 VAC
Power Consumption		1.0 W
Mounting		Surface - Ceiling
LED Life		100,000 hours
Photometric Classification		C0:D40 C90:D40
Battery Type		Ni-Cd
Height		68 mm
Width		167 mm
Depth		288 mm
Base Colour		Black
Battery Replacement		0301220
IP Rating		IP20
Standards Compliance		ASNZS CISPR 15 ASNZS2293.3:2018 ASNZS60598.1:2017 ASNZS60598.2.22:2005

Catalogue No: **SFB1LEDBLK**  
**SPITFIRE 1 LED SURFACE MOUNT BLACK**

Stanilite Emergency and Exit Lighting > Signature > Single Point Signature > Signature Spitfire EM



**REFERENCES**

IECEX Certificate -

Supplier Declaration of  
Conformity: -

Installation Guide: -

User Manual: -

Manufacturer Datasheet: -

Manufacturer Catalogue  
& Product Selection: -