

Platinum Exit LED Quickfit Vandal Resistant Pictograph



- Compliance to latest AS/NZS2293.3:2018.
- Reliable Stanilite Brand.
- LED energy efficient products.
- 10 year product design life.
- Lithium ion phosphate batteries.
- Advanced power management.

Representative Photo Only
(actual product may vary based on configuration selections)

SPECIFICATIONS

Component Type	Emergency Lighting	Exit
Testing System		Single Point Unit
Operating Mode		Maintained
Operating Voltage		240 VAC
Rated Frequency		50 Hz
Power Consumption		3.2 W
Mounting		Surface - Universal
Viewing Distance		24 meters
LED Life		100,000 hours
Photometric Classification		C0:E1.25 C90:E1.25
Battery Type		LiFePO4
Height		265 mm
Width		140 mm
Depth		410 mm
Base Colour		White
Diffuser Colour		White on Green
Battery Replacement		0301302P
IP Rating		IP20
IK Rating		IK09
Standards Compliance		AS/NZS CISPR 15 AS/NZS2293.3:2018 AS/NZS60598.1:2017 AS/NZS60598.2.22:2005

Catalogue No: **VPQLEDP**

PLATINUM EXIT LED QUICKFIT VANDAL RESISTANT PICTOGRAPH

Stanilite Emergency and Exit Lighting > Platinum > Single Point Platinum > Platinum Exit EM



REFERENCES

IECEX Certificate

-

Supplier Declaration of
Conformity:

[Quickfit LED Exit Sign, LifePO4 Battery_Supplier Declaration of Conformity \(SDoC\)](#)

Installation Guide:

[Exit LED Quickfit Vandal ResistantStandard, Nexus LX, Nexus RF](#)

User Manual:

-

Manufacturer Datasheet:

[Platinum Exit LED Quickfit Vandal Resistant_Manufacturer Datasheet](#)

Manufacturer Catalogue
& Product Selection:

-