Catalogue No: PLRNXSLEDP PLATINUM EXIT LED EDGELIT RECESSED NEXUS LX PICTO

Stanilite Emergency and Exit Lighting > Platinum > Monitored Platinum > Platinum Exit LX



\rightarrow

Representative Photo Only (actual product may vary based on configuration selections)

SPECIFICATIONS	
Component Type Emergency Lighting	Exit
Testing System	Nexus LX
Operating Mode	Maintained
Operating Voltage	240 VAC
Rated Frequency	50 Hz
Power Consumption	2.4 W
Mounting	Recessed
Viewing Distance	24 meters
LED Life	100,000 hours
Photometric Classification	C0:D3.2 C90 E2
Battery Type	LiFePO4
Height	164 mm
Width	120 mm
Depth	370 mm
Base Colour	White
Diffuser Colour	White on Green
Battery Replacement	0301304P
IP Rating	IP20
Standards Compliance	ASNZS CISPR 15 ASNZS2293.3:2018 ASNZS60598.1:2017

Platinum Exit LED Edgelit Recessed Nexus LX Picto

Reliable Stanilite Brand. LED energy efficient products.

10 year product design life.

Lithium ion phosphate batteries.

Advanced power management.

• •

•

•

•

Compliance to latest ASNZS2293.3:2018.

ASNZS60598.2.22:2005



Catalogue No: **PLRNXSLEDP**

PLATINUM EXIT LED EDGELIT RECESSED NEXUS LX PICTO

Stanilite Emergency and Exit Lighting > Platinum > Monitored Platinum > Platinum Exit LX

REFERENCES	
IECEx Certificate	
Supplier Declaration of Conformity:	Legend Recessed LED Exit Sign, NiMH or LifePO4 Battery_Supplier Declaration of Conformity (SDoC)
Installation Guide:	Stanilite Exit LED Edgelit Recessed Emergency, Nexus LX, Nexus RF_Installation Instructions
User Manual:	-
Manufacturer Datasheet:	Platinum Exit LED Edgelit Recessed NexusManufacturer Datasheet
Manufacturer Catalogue & Product Selection:	-



NHP