



Platinum Range Surface Mount Spitfire 2 LED



- Compliance to latest ASNZS2293.3:2018.
- Reliable Stanilite Brand.
- LED energy efficient products.
- 10 year product design life.
- Lithium ion phosphate batteries.
- Advanced power management.

Representative Photo Only  
(actual product may vary based on configuration selections)

SPECIFICATIONS	
Component Type	Emergency Lighting
Testing System	Spitfire
Operating Mode	Single Point Unit
Operating Voltage	Non-Maintained
Rated Frequency	240 VAC
Power Consumption	50 Hz
Mounting	1.0 W
LED Life	Surface - Ceiling
Photometric Classification	100,000 hours
Battery Type	C0:D63 C90:D63
Height	LiFePO4
Width	68 mm
Depth	167 mm
Base Colour	288 mm
Battery Replacement	White
IP Rating	0301303P
Standards Compliance	IP20
	ASNZS CISPR 15
	ASNZS2293.3:2018
	ASNZS60598.1:2017
	ASNZS60598.2.22:2005

Catalogue No: **SFB2LEDP**

**PLATINUM RANGE SURFACE MOUNT SPITFIRE 2 LED**

Stanilite Emergency and Exit Lighting > Platinum > Single Point Platinum > Platinum Spitfire EM



#### REFERENCES

IECEX Certificate -

Supplier Declaration of  
Conformity: -

Installation Guide: -

User Manual: -

Manufacturer Datasheet: [Platinum Spitfire LED Surface Mount Non-maintained\\_Manufacturer Datasheet](#)

Manufacturer Catalogue  
& Product Selection: -