



Platinum Batten IP44 1200mm Maintaned EM 4600 lumens



- Compliance to latest ASNZS2293.3:2018.
- Reliable Stanilite Brand.
- LED energy efficient products.
- 10 year product design life.
- Lithium ion phosphate batteries.
- Advanced power management.

Representative Photo Only
(actual product may vary based on configuration selections)

SPECIFICATIONS

Component Type	Emergency Lighting	Batten
Testing System		Single Point Unit
Operating Mode		Maintained
Operating Voltage		240 VAC
Rated Frequency		50 Hz
Power Consumption		43.0 W
Mounting		Surface - Universal
LED Life		50,000 hours
Lumen Output		4600 lumens
Photometric Classification		C0:D80 C90:D50
Battery Type		LiFePO4
Height		65 mm
Width		80 mm
Depth		1200 mm
Base Colour		White
Diffuser Colour		Frosted
Battery Replacement		0301227
IP Rating		IP40
IK Rating		IK06
Standards Compliance		ASNZS CISPR 15 ASNZS2293.3:2018 ASNZS60598.1:2017 ASNZS60598.2.22:2005

Catalogue No: **PBL4EM46LM**

PLATINUM BATTEN IP44 1200mm MAINTANED EM 4600lm

Stanilite Emergency and Exit Lighting > Platinum > Single Point Platinum > Platinum Batten EM



REFERENCES

IECEX Certificate

-

Supplier Declaration of
Conformity:

-

Installation Guide:

[Stanilite Platinum Batten LED AC, Standard, Nexus LX, Nexus RF_Installation Instructions](#)

User Manual:

-

Manufacturer Datasheet:

[Platinum Batten LED - 4 Foot_Manufacturer Datasheet](#)

Manufacturer Catalogue
& Product Selection:

-