

Platinum Exit LED Edgelit Quickfit Pictograph 1 Box Solution

- Compliance to latest ASNZS2293.3:2018.
- Reliable Stanilite Brand.
- LED energy efficient products.
- 10 year product design life.
- Lithium ion phosphate batteries.
- Advanced power management.



Representative Photo Only
(actual product may vary based on configuration selections)

SPECIFICATIONS

Component Type	Emergency Lighting	Exit
Testing System		Single Point Unit
Operating Mode		Maintained
Operating Voltage		240 VAC
Rated Frequency		50 Hz
Power Consumption		2.4 W
Mounting		Surface - Universal
Viewing Distance		24 meters
LED Life		100,000 hours
Photometric Classification		C0:D3.2 C90:DE2
Battery Type		LiFePO4
Height		232 mm
Width		72 mm
Depth		379 mm
Base Colour		White
Diffuser Colour		White on Green
Battery Replacement		0301305P
IP Rating		IP20
Standards Compliance		ASNZS CISPR 15 ASNZS2293.3:2018 ASNZS60598.1:2017 ASNZS60598.2.22:2005



REFERENCES

IECEX Certificate

-

Supplier Declaration of
Conformity:

[Quickfit LED Exit Sign, LifePO4 Battery_Supplier Declaration of Conformity \(SDoC\)](#)

Installation Guide:

[Stanilite Exit LED Edgelit Quickfit Emergency, Nexus LX, Nexus RF_Installation Instructions](#)

User Manual:

-

Manufacturer Datasheet:

[Platinum Exit LED Edgelit Quickfit_Manufacturer Datasheet](#)

Manufacturer Catalogue
& Product Selection:

-