

## ECO LED Batten Gen 3

The ECO LED Batten Gen 3 is a one box solution with Colour Select across the range and the new Lumen Select option is now available in the 4ft version. The quick release clips and removable connector, insect-proof sealed LED module makes it easy to install and maintain. With up to 110lm/W, the efficacy makes it an ideal replacement for traditional battens.

- Increased visual comfort with less than 1% flicker
- · Easy to install with larger 4mm terminal block and rear cable entry
- · Opalised diffuser for even light distribution



LUMEN SELECT COLOUR SELECT















Lifetime







CRI

Ingress Protection Rating

Impact Rating

MacAdam Steps

Operating Temperature

**Dimming** 

Warranty

Beam Distribution

Beam Angle

CODE	SYSTEM POWER	EXIT LUMEN	EFFICACY	CCT	DIMENSIONS	WEIGHT	LINE CURRENT
ECOBAT202ECSG3	18W	1700lm	94lm/W	4000K	L603 x W74 x H74mm	0.80kg	0.07A
		1900lm		5000K			
		1700lm		6500K			
ECOBAT404ECSLS	36W	3600lm	100lm/W	4000K	L1164 x W74 x H74mm	2kg	0.15A
	18W	2180lm		4000K			
	18W	2300lm		5000K			
	18W	2190lm		6500K			
	25W	2700lm		4000K			
	25W	2960lm		5000K			
	25W	2770lm		6500K			
	30W	3200lm		4000K			
	30W	3600lm		5000K			
	30W	3300lm		6500K			
	36W	4100lm		5000K			
	36W	3700lm		6500K			
ECOBAT505ECSLS	50W	6440lm	128lm/W	4000K	L1500 x W74 x H74mm	2kg	0.22A
	30W	4042lm	134lm/W	4000K			
	30W	4149lm	138lm/W	5000K			
	30W	3962lm	132lm/W	6500K			
	35W	4974lm	142lm/W	4000K			
	35W	5159lm	147lm/W	5000K			
	35W	4877lm	139lm/W	6500K			
	45W	5788lm	128lm/W	4000K			
	45W	5996lm	133lm/W	5000K			
	45W	5607lm	124lm/W	6500K			



ECOBAT505ECSLS

ACCESSORY CODE


50W 50W 6769lm 6737lm 135lm/W 134lm/W 5000K

6500K

DESCRIPTION

WG4 W/GUARD 1200MM C/W BRACKETS
WG2 W/GUARD 600MM C/W BRACKETS

**Line Drawings** 





ECOBAT202ECSG3

ECOBAT404ECSLS



## ECOBAT505ECSLS

## **Product Images**

