





PREMIER S9074TC / HP - 10W

LED downlight with selectable CCT, IP64

Application

Ideal for any residential or commercial interior spaces looking for an economical lighting choice

Design Specifications

- Premium aluminium body, IC-4 rated
- Selectable CCT 3000K / 4000K / 5700K
- Stylish white trim
- Recessed opal polycarbonate diffuser
- High efficiency LED optics CRI>90
- Trailing edge dimmable driver, with flickerCONTROL technology and flex and plug

Performance

- Dimmable YES
- Dimmer Type Trailing edge, optional 1-10V, DALI / DSI































Technical Specification

| Product | Model No. | Input Voltage (V/AC) | Power (W) | Lumens (lm) | ССТ (К) | Beam Angle (°) |
|---------|---------------|-------------------------|--------------|----------------|----------------|-------------------|
| | S9074TC/WH/HP | 240 | 10 | 1000/1100/1000 | 3000/4000/5700 | 90 |

| Dimmable | CRI | Body Colour | Cut Out (mm) | Diameter (mm) | Dim (mm) | IPART |
|----------|-----|-------------|--------------|---------------|----------|-------|
| YES | 90 | WHITE | 160 | 200 | 68(H) | YES |

| DETC. | |
|-------|--|
| REES | |
| YES | |

Due to continued product and technology enhancements, data sourced from sal.net.au shall not form part of any contract and or technical performance guarantee unless expressly confirmed in writing by SAL at the time of order. Products are sold in accordance with SAL Terms and Conditions of sale and all images shown are for illustration purposes only and may vary from the actual colour or finish. Unless specifically stated, all IP ratings nominated for Interior products are from "below the ceiling".





Dimensions

S9074TC

