



ECOGEM S9041TC - 10W

Dimmable IP44 LED downlight with selectable colour temperature

Application

Ideal for any residential or commercial interior space

Design Specifications

- Easy selectable colour temperature with an inbuilt DIP switch, IC - 4 rated
 - Durable die-cast aluminium square body profile
 - Trim colour choice of white or satin nickel
 - Remote constant current trailing edge dimmable LED driver, with flex and plug
 - High efficiency SMD LED chips and quality opal polycarbonate diffuser.
- High performance, HO 13W model available to order

Performance

- Dimmable - **YES**
- Dimmer Type - **Trailing edge, optional 1-10V, DALI / DSI**



Technical Specification

Product	Model No.	Input Voltage (V/AC)	Power (W)	Lumens (lm)	CCT (K)	Beam Angle (°)
	S9041 TC S WH	240	10	800/900/850	3000/4200/5700	90
	S9041 TC S SN	240	10	800/900/850	3000/4200/5700	90


Dimmable	CRI	Body Colour	Cut Out (mm)	Dim (mm)	iPART	REES
YES	80	WHITE	92	104(L) x 104(W) x 40(H)	YES	YES
YES	80	SATIN NICKEL	92	104(L) x 104(W) x 40(H)	YES	YES

Due to continued product and technology enhancements, data sourced from sal.net.au shall not form part of any contract and or technical performance guarantee unless expressly confirmed in writing by SAL at the time of order. Products are sold in accordance with [SAL Terms and Conditions of sale](#) and all images shown are for illustration purposes only and may vary from the actual colour or finish. Unless specifically stated, all IP ratings nominated for Interior products are from "below the ceiling".

Dimensions




Dimensions



Photometric Data

Unit: cd C0/C180 — C30/C210 —
cd C60/C240 — C90/C270 —

S9041 TC S at 3000K



THE SFI SYSTEM ELIMINATES LED FLICKERING.

**SIMPLY
MATCH THE
ECO GEM SFI
DOWNLIGHT
WITH THIS
SDD400SFI
DIMMER.**



**DIM with
FLICKER
CONTROL**

For related
products
please
scan me

